

Date		Project	
Type		Part Number	

PRIME R ALL-IN-ONE PERFORMANCE LIGHTING

EMERGENCY Series

Emergency Battery

These battery units are designed with a rugged metal frame and sporting double swivel positioning heads on top to provide bright illumination. Easy knockouts provided for swift installation on each jobsite.



PRODUCT FEATURES

- 120/277/347V input with any emergency lighting system (5-24VDC)
- Lead Acid Battery
- Self-powered for 120 minutes
- Max remote load :
 - 72W at 30 mins battery backup time
 - 27W at 90 mins battery backup time
 - 22W at 120 mins battery backup time
- Operating Temperature: 50°F - 104°F (10°C - 40°C)
- 5 year warranty

KEY SPECIFICATIONS

Input Voltage	120/277/347V
Output Voltage	6VDC or 12VDC
Head Wattage	2 x 2W or 2 x 5W
Power	36W or 72W
Recharge Time	24 Hours
Discharge Time	Up to 120 Minutes
Applications	Commercial, Warehouse, Retail Facilities

SPECIFICATIONS

Order#	Model	Wattage	Head Power	Discharge Time	Input Voltage	Output Voltage
R61201	RENO-EBP36W-U	36W	2 x 2W	Up to 120 Minutes	120/277/347V	6V
R61202	RENO-EBP72W-U	72W	2 x 5W	Up to 120 Minutes	120/277/347V	12V

ACCESSORIES – REMOTE HEADS



R61101
RENO-ERH2W-1
Single Head Emergency Light



R61106
RENO-ERH5W-1
Single Head Emergency Light



R61103
RENO-ERH2W-2
Double Head Emergency Light



R61105
RENO-ERH5W-2
Double Head Emergency Light

Order#	Model	Description
R61101	RENO-ERH2W-1	Single Head Emergency Light 2W
R61106	RENO-ERH5W-1	Single Head Emergency Light 5W
R61103	RENO-ERH2W-2	Double Head Emergency Light 2 x 2W
R39303	RENO-ERH5W-2	Double Head Emergency Light 2 x 5W

DIMENSIONS

