PRIME R

ALL-IN-ONE PERFORMANCE LIGHTING

TYPE C T5

Multi-CCT Type C T5 Tubes

Upgrade your lighting system with T5 Type C LED lamps, designed for maximum efficiency, longevity, and performance. Featuring an external driver system, these LEDs offer greater reliability, reduced energy consumption, and an extended lifespan of up to 50,000 hours. Perfect for offices, schools, hospitals, warehouses, and commercial buildings, they deliver consistent, flicker-free illumination while lowering maintenance costs.

UL CERTIFIED · MULTI CCT · NSF · 10 YEARS LIMITED WARRANTY

PRODUCT FEATURES

- NSF Listed: NSF/ANSI Standard 2 - Food Equipment
- Suitable for use in dry and damp locations
- Suitable for open fixtures
- Direct plug-in & Safe Installation
- No UV or IR radiation
- Compatible with any Type C driver and **RENO's DALI Driver**
- Dimming based on Driver parameters
- Operating temperature: -4°F to +113°F (-20°C to +45°C)
- Rated Lifetime L70(hrs): >100,000
- 10 year limited warranty

KEY SPECIFICATIONS

Voltage	BF
Lamp Base	G5
Wattage	13-25W
Length	4FT
Efficacy	Up to 138 lm/W
Lumens	Up to 3,400lm
CCT	3000K or 3500K or 4000K or 5000K or 6500K
CRI	>83
Beam Angle	330°
Certifications	UL, NSF
Applications	Commercial, Residential, Office, Food Service Facilities

SPECIFICATIONS

Order#	Model	Size	Wattage	Voltage	CCT	Lumens	Beam Angle
R42202	RENO-LEDT5EX13W-MCCT	4.0 ft	13W	BF	30/35/40/50/65K	1,800 lm	330°
R42203	RENO-LEDT5EX25W-MCCT	4.0 ft	25W	BF	30/35/40/50/65K	3,400 lm	330°

ACCESSORIES – MOUNTING

R83101
LED ISO adjustable power driver

Order#	Model	Description
R83101	RENO-DA54B-DV-PS	LED ISO adjustable power driver

DIMENSIONS

4 FT

Full Body Width

Thickness

Lens Width

Full Body Width: 45.2" (1148.1 mm)

Lens Width: 40.6" (1031.2 mm)

Thickness: 0.9" (22.9 mm)

Weight: n/a