





## HALF ROUND WALL SCONCE



# A DASH OF CINEMA

The Cinema Series Semi-Circle Wall Pack is designed to be a statement piece that transforms your outdoor space with cinematic charm. With its sleek, curved design and energy-efficient brilliance, it creates a soft, ambient glow that brings sophistication and style to every moment.



### KEY FEATURES

- Up to 11,600 lumens and 145 lm/W
- Two Multi Power models: R1 (24/32/40W), R2 (48/64/80W)
- Multi CCT feature, easily select between 3000K, 4000K, or 5000K
- Easily switch between two different lighting configurations: down or full (up and down)
- Includes built-in DC photocell
- IP65 rated and saltwater-resistant

## **CREATED FOR** CURVE APPEAL



#### **RESIDENTIAL EXTERIORS**

Illuminate front porches, patios, balconies, or garden walls while enhancing curb appeal.

#### **COMMERCIAL SPACES**

Create a welcoming and stylish ambiance for cafes and boutique storefronts, drawing attention to entrances or outdoor seating areas. A design solution that transforms any environment with its cinematic glow and modern curves, the CINEMA Series enhances, highlights, and elevates the exterior of any space.



#### **HOSPITALITY SETTINGS**

Add a touch of elegance to walkways, poolside areas, or building facades, creating a luxurious and inviting atmosphere for hotels, resorts, and spas.

#### ARCHITECTURAL ACCENT

Highlight unique architectural features, such as columns, textured walls, or modern facades, providing a dramatic effect that emphasizes the design of a space.

## **CONTROL FULL OR DOWN**



#### DOWN ONLY LIGHT

Designed to emit light downwards only provide focused, glare-free illumination ideal for pathways, entryways, and accent walls.





#### FULL (UP & DOWN) LIGHT

Dual-beam design adds depth, warmth, and ambiance to walls, making them perfect for both modern and classic settings.





**SPECIFICATIONS** 

Order#	Model Number	Wattge	Voltage	Lumens	ССТ
R51051	RENO-UDSWP-MW-DV-MCCT-R1	24W / 32W / 40W	120-347V	up to 5,800 lm	30 / 40 / 5000K
R51052	RENO-UDSWP-MW-DV-MCCT-R2	48W / 64W / 80W	120-347V	up to 11,600 lm	30 / 40 / 5000K



#### **EMERGENCY LED DRIVER OPTION**

Order#	Model Number	Description	
R83010	RENO-EM-EX15	External Mount Emergency Driver, All Weather	





US Office 8735 Dunwoody Place #6728 Atlanta, GA 30350 United States



**CA Office** 9133 Leslie St. #120 Richmond Hill, ON L4B 4N1 Canada

info@renolighting.com | www.renolighting.com