



TITLE 20/24 (JA8) LAMPS : E26 BASE

DESCRIPTION

These LED lamps are designed to meet or exceed the standards set out in the California Energy Commission's Title 20 and Title 24 (JA8) Appliance Efficiency Regulations.

FEATURES

- A-line, BR, and PAR lamps with E26 base
- 80% more efficient and 30x longer life than standard incandescent
- Shatter-resistant plastic housing for reduced risk of injury and breakage
- Compatible with a wide array of dimmers
- ANSI construction compliant

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Restaurants & Hospitality
- Retail
- Residential
- Accent/Display Lighting
- Healthcare



PERFORMANCE	Bulb	A19		BR20	BR30	BR40	PAR20	PAR30	PAR38
	Power Consumption	9W	12W	5.5W	9W	11W	5.5W	10W	12W
	Lumens	800	1,100	525	800	1,000	500	900	1,100
	Efficacy (LPW)	88.9	91.7	95.5	88.9	90.9	90.9	90	92
	CRI	90+							
	CCT	2700K/3000K							
	Life (L70)	25,000 hours							
	Power Factor	>0.7							
ELECTRICAL	Input Voltage	120V							
	Operating Temperature	-4°F to 104°F (-20°C to 40°C)							
CONSTRUCTION	Base	E26							
	Certification(s)	Title 20 and Title 24 (JA8) Compliant; cULus Classified							
LISTINGS	Material Usage	RoHS Compliant; no mercury or lead							
	Environment	Suitable for damp locations; Enclosed fixture rated (select items); Not for use with electronic timers, photocells, or motion/occupancy sensors							

PERFORMANCE SUMMARY

A19 E26 BASE:

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	MOL	MOD	Life/Hours	Replaces Incan.
10543	LED9WA19/OMN/927-DIM-G9	800	9W	89	2700K	90+	4.25"	2.36"	25,000	60W
10544	LED9WA19/OMN/930-DIM-G9	800	9W	89	3000K	90+	4.25"	2.36"	25,000	60W
10545	LED12WA19/OMN/927-DIM-G9	1,100	12W	92	2700K	90+	4.61"	2.36"	25,000	75W
10546	LED12WA19/OMN/930-DIM-G9	1,100	12W	92	3000K	90+	4.61"	2.36"	25,000	75W

NOTE: Use order code when ordering.

BR E26 BASE:

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	MOL	MOD	Life/Hours	Replaces Incan.
10547	LED5.5WBR20/927-DIM-G9	525	5.5W	96	2700K	90+	3.82"	2.5"	25,000	55W
10548	LED5.5WBR20/930-DIM-G9	525	5.5W	96	3000K	90+	3.82"	2.5"	25,000	55W
10549	LED9WBR30/927-DIM-G9	800	9W	89	2700K	90+	5.12"	3.74"	25,000	65W
10550	LED9WBR30/930-DIM-G9	800	9W	89	3000K	90+	5.12"	3.74"	25,000	65W
10551	LED11WBR40/927-DIM-G9	1,000	11W	91	2700K	90+	6.26"	4.72"	25,000	65W
10552	LED11WBR40/930-DIM-G9	1,000	11W	91	3000K	90+	6.26"	4.72"	25,000	65W

NOTE: Use order code when ordering.

PAR E26 BASE:

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.
10553	LED5.5WPAR20/FL/927-DIM-G9	500	5.5W	91	2700K	90+	43°	3.15"	2.48"	25,000	55W
10554	LED5.5WPAR20/FL/930-DIM-G9	500	5.5W	91	3000K	90+	44.5°	3.15"	2.48"	25,000	55W
10555	LED10WPAR30/FL/927-DIM-G9	900	10W	90	2700K	90+	43°	4.53"	3.74"	25,000	75W
10556	LED10WPAR30/FL/930-DIM-G9	900	10W	90	3000K	90+	43°	4.53"	3.74"	25,000	75W
10557	LED12WPAR38/FL/927-DIM-G9	1,100	12W	92	2700K	90+	41.9°	5.12"	4.72"	25,000	120W
10558	LED12WPAR38/FL/930-DIM-G9	1,100	12W	92	3000K	90+	41.9°	5.12"	4.72"	25,000	120W

NOTE: Use order code when ordering.

DIMENSIONS

A19



	MOL	MOD
9W A19	4.25"	2.36"
12W A19	4.61"	2.36"

BR



	MOL	MOD
5.5W BR20	3.82"	2.5"
9W BR30	5.12"	3.74"
11W BR40	6.26"	4.72"

PAR



	MOL	MOD
5.5W PAR20	3.15"	2.48"
10W PAR30	4.53"	3.74"
12W PAR38	5.12"	4.72"