



A19 REPLACEMENT : E26 & GU24 BASE

DESCRIPTION

LED A-Line Replacement Lamps directly replace incandescent A lamps at a fraction of the energy cost.

FEATURES

- Direct replacement for 40W, 60W, 75W, or 100W incandescent A-lamps
- 240° beam angle is ideal for table lamps, wall sconces, and luminous globe fixtures
- 80% more efficient and 30x longer life than standard incandescent
- Shatter-resistant plastic housing for reduced risk of injury and breakage
- Dimmable models compatible with a wide array of dimmers
- ANSI construction compliant
- Not for use with electronic timers, photocells, or motion/occupancy sensors

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Restaurants & Hospitality
- Retail
- Residential
- Accent/Display Lighting
- Healthcare



A19 E26



A19 GU24



| | | | | | |
|---------------------|-----------------------|---|------|-------|-------|
| PERFORMANCE | Power Consumption | 6W | 9W | 11W | 15W |
| | Lumens | 480 | 800 | 1,100 | 1,600 |
| | Efficacy (LPW) | 80 | 88.9 | 100 | 106.7 |
| | CRI | 80+ | | | |
| | Beam | 240° | | | |
| | CCT | 2700K/3000K/4000K/5000K | | | |
| | Life (L70) | | | | |
| ELECTRICAL | Power Factor | >0.7 | | | |
| | Input Voltage | 120V | | | |
| CONSTRUCTION | Operating Temperature | -4°F to 104°F (-20°C to 40°C) | | | |
| | Base | E26/GU24 | | | |
| LISTINGS | Certification(s) | cULus Classified | | | |
| | Material Usage | RoHS Compliant; no mercury or lead | | | |
| | Environment | Suitable for damp locations; Enclosed fixture rated | | | |

PERFORMANCE SUMMARY

A19 MEDIUM BASE (E26):

| Order Code | Item # | Lumens | Watts | LPW | CCT | CRI | Beam | MOL | MOD | Life/Hours | Replaces Incan. |
|------------|-------------------------|--------|-------|-------|-------|-----|------|-------|-------|------------|-----------------|
| 10559 | LED6WA19/OMN/827-DIM-A | 480 | 6W | 80 | 2700K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 40W A19 |
| 10560 | LED6WA19/OMN/830-DIM-A | 480 | 6W | 80 | 3000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 40W A19 |
| 10561 | LED6WA19/OMN/840-DIM-A | 480 | 6W | 80 | 4000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 40W A19 |
| 10562 | LED9WA19/OMN/827-A | 800 | 9W | 88.9 | 2700K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 60W A19 |
| 10563 | LED9WA19/OMN/830-A | 800 | 9W | 88.9 | 3000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 60W A19 |
| 10564 | LED9WA19/OMN/840-A | 800 | 9W | 88.9 | 4000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 60W A19 |
| 10565 | LED9WA19/OMN/850-A | 800 | 9W | 88.9 | 5000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 60W A19 |
| 10566 | LED9WA19/OMN/827-DIM-A | 800 | 9W | 88.9 | 2700K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 60W A19 |
| 10567 | LED9WA19/OMN/830-DIM-A | 800 | 9W | 88.9 | 3000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 60W A19 |
| 10569 | LED9WA19/OMN/840-DIM-A | 800 | 9W | 88.9 | 4000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 60W A19 |
| 10574 | LED9WA19/OMN/850-DIM-A | 800 | 9W | 88.9 | 5000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 60W A19 |
| 10581 | LED11WA19/OMN/827-DIM-A | 1,100 | 11W | 100 | 2700K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 75W A19 |
| 10583 | LED11WA19/OMN/830-DIM-A | 1,100 | 11W | 100 | 3000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 75W A19 |
| 10584 | LED11WA19/OMN/840-DIM-A | 1,100 | 11W | 100 | 4000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 75W A19 |
| 10586 | LED11WA19/OMN/850-DIM-A | 1,100 | 11W | 100 | 5000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 75W A19 |
| 10598 | LED15WA19/OMN/827-DIM-A | 1,600 | 15W | 106.7 | 2700K | 80+ | 240° | 4.6" | 2.36" | 25,000 | 100W A19 |
| 10600 | LED15WA19/OMN/830-DIM-A | 1,600 | 15W | 106.7 | 3000K | 80+ | 240° | 4.6" | 2.36" | 25,000 | 100W A19 |
| 10601 | LED15WA19/OMN/840-DIM-A | 1,600 | 15W | 106.7 | 4000K | 80+ | 240° | 4.6" | 2.36" | 25,000 | 100W A19 |
| 10603 | LED15WA19/OMN/850-DIM-A | 1,600 | 15W | 106.7 | 5000K | 80+ | 240° | 4.6" | 2.36" | 25,000 | 100W A19 |

A19 GU24 BASE:

| Order Code | Item # | Lumens | Watts | LPW | CCT | CRI | Beam | MOL | MOD | Life/Hours | Replaces Incan. |
|------------|------------------------------|--------|-------|------|-------|-----|------|-------|-------|------------|-----------------|
| 10575 | LED9WA19/OMN/827-GU24-DIM-A | 800 | 9W | 88.9 | 2700K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 60W A19 |
| 10577 | LED9WA19/OMN/830-GU24-DIM-A | 800 | 9W | 88.9 | 3000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 60W A19 |
| 10578 | LED9WA19/OMN/840-GU24-DIM-A | 800 | 9W | 88.9 | 4000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 60W A19 |
| 10589 | LED11WA19/OMN/827-GU24-DIM-A | 1,100 | 11W | 100 | 2700K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 75W A19 |
| 10591 | LED11WA19/OMN/830-GU24-DIM-A | 1,100 | 11W | 100 | 3000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 75W A19 |
| 10594 | LED11WA19/OMN/840-GU24-DIM-A | 1,100 | 11W | 100 | 4000K | 80+ | 240° | 4.25" | 2.36" | 25,000 | 75W A19 |

NOTE: Use order code when ordering.

DIMENSIONS

