



# Pro Line Family of LED Lamps

## Product Specifications



For an affordable LED upgrade, switch to TCP's Pro Line LED Lamps. Pro Line LEDs are available in both SMD and Filament technology, across a full range of lamp shapes, from A-Lamps, to BR30 and PAR38 lamps. See how you can maximize savings and minimize maintenance costs with Pro Line LED Lamps.

### Reasons to choose the Pro Line LED Lamps from TCP

- Long-life: 15,000 hours minimizes replacement and maintenance costs
- Inexpensive alternative for cost-sensitive projects
- ANSI Construction Compliant to fit most general applications
- Dimmable
- UL approved for damp location means lamps can be used outdoors when protected from the elements

### Ideal Applications

- Commercial
- Retail
- Industrial
- Residential

### Specifications

Input Line Voltage ..... 120 VAC  
 Input Line Frequency..... 50/60HZ  
 Lamp Life (Rated) ..... 15,000 hours  
 Dimmable..... Yes

CRI..... 80  
 Base..... E26, E12  
 Warranty..... 3 Years



## Specifications



A19 40W  
E26 Base



A19 60W  
E26 Base



A19 75W  
E26 Base



A19 100W  
E26 Base

ITEM #	ITEM DESCRIPTION	WATTS	INCAN WATTS	CRI	LUMENS	LPW	COLOR TEMP	CASE QTY
<b>A19 • Dimmable • 15,000 Hours • E26 Base</b>								
FPA19D40E26CL27K	Pro Line Filament 40W A19 27K CLR	4.5	40	80	450	100	2700K	12
FPA19D40E26CL30K	Pro Line Filament 40W A19 30K CLR	4.5	40	80	450	100	3000K	12
FPA19D40E26CL41K	Pro Line Filament 40W A19 41K CLR	4.5	40	80	450	100	4100K	12
FPA19D40E26CL50K	Pro Line Filament 40W A19 50K CLR	4.5	40	80	450	100	5000K	12
FPA19D60E26CL27K	Pro Line Filament 60W A19 27K CLR	7	60	80	800	114.2	2700K	12
FPA19D60E26CL30K	Pro Line Filament 60W A19 30K CLR	7	60	80	800	114.2	3000K	12
FPA19D60E26CL41K	Pro Line Filament 60W A19 41K CLR	7	60	80	800	114.2	4100K	12
FPA19D60E26CL50K	Pro Line Filament 60W A19 50K CLR	7	60	80	800	114.2	5000K	12
FPA19D75E26CL27K	Pro Line Filament 75W A19 27K CLR	10.5	75	80	1100	104.7	2700K	12
FPA19D75E26CL30K	Pro Line Filament 75W A19 30K CLR	10.5	75	80	1100	104.7	3000K	12
FPA19D75E26CL41K	Pro Line Filament 75W A19 41K CLR	10.5	75	80	1100	104.7	4100K	12
FPA19D75E26CL50K	Pro Line Filament 75W A19 50K CLR	10.5	75	80	1100	104.7	5000K	12
FPA19D100E26CL27K	Pro Line Filament 100W A19 27K CLR	14.5	100	80	1600	110.3	2700K	6
FPA19D100E26CL30K	Pro Line Filament 100W A19 30K CLR	14.5	100	80	1600	110.3	3000K	6
FPA19D100E26CL41K	Pro Line Filament 100W A19 41K CLR	14.5	100	80	1600	110.3	4100K	6
FPA19D100E26CL50K	Pro Line Filament 100W A19 50K CLR	14.5	100	80	1600	110.3	5000K	6

## Specifications



ITEM #	DESCRIPTION	WATTS	INCAND. WATTS	CRI	LUMENS	LPW	COLOR	FINISH	HOURS	MOL (inches)	DIA (inches)	BASE	WARRANTY YEARS	CASE QTY
<b>LED All Glass A-LAMP • 15,000 Hour</b>														
<b>4.5W A19 • Dimmable</b>														
LFF40A19D1527K	LED 40W EQ GLASS A19 DIM 27K FR	4.5	40	80	425	94.4	2700K	FROST	15,000	4.2	2.4	E26	3	12
LFC40A19D1527K	LED 40W EQ GLASS A19 DIM 27K CL	4.5	40	80	425	94.4	2700K	CLEAR	15,000	4.2	2.4	E26	3	12
<b>8W A19 • Dimmable</b>														
LFF60A19D1550K	LED 60W EQ GLASS A19 DIM 50K	8	60	80	725	90.6	5000K	FROST	15,000	4.2	2.4	E26	3	12
<b>8W A19 • Non-Dimmable</b>														
LFC60A19N1527K	LED 60W EQ GLASS A19 ND 27K CL	8	60	80	725	90.6	2700K	CLEAR	15,000	4.2	2.4	E26	3	12
LFC60A19N1550K	LED 60W EQ GLASS A19 ND 50K CL	8	60	80	725	90.6	5000K	CLEAR	15,000	4.2	2.4	E26	3	12
<b>LED All Glass Decorative 40W Equivalent • Dimmable • 15,000 Hour</b>														
FG25D40V27W	LED 4W G25 DIM 27K FR PRO LINE	4	40	80	350	87.5	2700K	FROST	15,000	4.5	3.2	E26	3	12
<b>LED A-LAMP • 15,000 Hour</b>														
<b>14W A19 • Non-Dimmable</b>														
L100A19N15V27K	LED 14W A19 ND 27K PRO LINE	14	100	80	1500	107.1	2700K	FROST	15,000	4.5	2.6	E26	3	12
<b>LED BR • Dimmable • 15,000 Hour</b>														
L50R20D15V27K	LED 7W R20 DIM 27K PRO LINE	7.5	50	80	500	66.7	2700K	FROST	15,000	3.8	2.5	E26	3	12
L65BR30D15V27K	LED 9W BR30 DIM 27K PRO LINE	9	65	80	665	73.9	2700K	FROST	15,000	4.8	3.7	E26	3	12
L75BR40D15V27K	LED 14W BR40 DIM 27K PRO LINE	14	75	80	1065	76.1	2700K	FROST	15,000	5.6	7.3	E26	3	12
<b>LED PAR* • Dimmable • 15,000 Hour</b>														
L50P20D15V30KFL	LED 7W P20 DIM 30K FL PRO LINE	7	50	80	525	75	3000K	FROST	15,000	3.4	2.3	E26	3	12
L75P30D15V30KFL	LED 10W P30 DIM 30K FL PRO LINE	9	75	80	720	80	3000K	FROST	15,000	4.8	3.9	E26	3	12
L90P38D15V30KFL	LED 13W P38 DIM 30K FL PRO LINE	13	90	80	1100	84.6	3000K	FROST	15,000	5.3	4.8	E26	3	12

\* ALL PAR LAMPS HAVE A 40° BEAM ANGLE AND ARE SUITABLE FOR WET LOCATIONS.

SUGGESTED DIMMER COMPATIBILITY	
MANUFACTURER	MODEL NUMBER
Leviton	R50-IPLO6-10M
	R61-06674-POI
Lutron	CTCL-153PDH-WH
	TGCL-153PH-WH
	DVVCL-153PH-WH

Note: E26 compatible dimmer

# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcp.com](http://tcp.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516