

# Technical Information Bulletin

## LED Linear Tubes



Date: \_\_\_\_\_ Name of distributor: \_\_\_\_\_  
In hands date of project: \_\_\_\_\_ Client #: \_\_\_\_\_  
Project name/Number: \_\_\_\_\_ Name of end user: \_\_\_\_\_

### ORDERING INFORMATION

Order code: 67377  
Description: T8/15W/835/48/BYP/277-347/ND/STD  
UPC: 69549673779  
Case quantity: 25



MOL: 48 in. (1 200 mm) Dia.: 1 in. (26 mm)

### PHYSICAL DATA

Shape: T8  
Base: G13  
Material: Glass

### PERFORMANCE DATA

Install method: Ballast bypass  
Lamp Watts (W): 15  
Volts (VAC): 277-347  
Colour temperature (K)<sup>1</sup>: 3 500  
Initial Lumens (lm)<sup>2</sup>: 2 000  
Initial lumens per watt (lm/W): 133  
Life L70 (hrs): 50 000  
CRI: 82  
Operating temperature range: -25°C to 45°F (-13°C to 113°F)

<sup>1</sup> Typical colour temperature range: +/- 5 %

<sup>2</sup> Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %



NON-DIMMABLE



DAMP



ENCLOSED  
FIXTURE



COMPLIANT



NO  
MERCURY



WARRANTY



C UL US



\*This product complies with UL1598C Standard for LED luminaire Retrofit kits. Not suitable for hazardous location.

### ADDITIONAL INFORMATION

ONLY FOR BALLAST BYPASS INSTALLATION IN 277-347V APPLICATIONS. NOT FOR USE IN 120V DIRECT LINE VOLTAGE APPLICATIONS.  
Direct replacement for 25, 28, 30 & 32 watts T8 lamps only.

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: \_\_\_\_\_

Company: \_\_\_\_\_

Signature: \_\_\_\_\_

Date: \_\_\_\_\_

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.  
Data is based upon tests performed in a controlled environment and representative of relative performance.  
Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

November 28, 2018