

Project:		Type:
Drawn by:	Catalogue #:	Date:

# Individual Spec Sheet

# **LOW VOLTAGE LED TAPE**

4.4 W, 24 V - IP22

#### ORDERING INFORMATION

Order code: 65889

**Description:** TAPE/16.4'/4.4W/30K/24V/IP22/180/8MM/STD

UPC: 069549658899

Case quantity:

#### **PHYSICAL DATA**

Reel Total Length: 16.4 ft. (5 m) Jacketed or Unjacketed: Unjacketed 22 AWG Wire gauge:

Number of LEDs: 180 LEDs per meter

55 LEDs per foot

**Cuttable length:** 1  $\frac{5}{16}$  in (33.3 mm) or every 6 LED chips

Maximum run length: 23 ft. (7 m)

**Operating Temperature:** -25°C / -13°F to 40°C / 104°F

## PERFORMANCE DATA

Volts (V DC):

Color temperature (K): 3 000 (Neutral white) Watts per length: 73 W per reel

> 14.5 W per meter 0.37 W per inch

Light output per length: 4 920 lm per reel

> 984 Im per meter 25 lm per inch

Efficacy (Im/W): 68 CRI: 90+ Life (hrs): 50 000 Beam angle (°): 120

1 Typical Color temperature range: +/- 5 %

<sup>2</sup> Lumen values are derived from photometric testing. Initial lumens range: +/- 5 %

<sup>3</sup> Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations

Extrusions, drivers and accessories are available (sold seperatly). Custom lenghts available upon request. Ask your sales representative for more information. This LED Tape is also available in 1.5 W and 2.9 W.











dry location




This lighting equipment complies with Canadian standard ICES-005 for use in residential applications. Data is based upon tests performed in a controlled environment.

Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.





## **DIMENSIONS**





Qty	Description	Price	
Name:	ations of the luminaire configuration mentioned above.		
Company: Signature:			
Signature:		Date:	

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

