



MR16

MOL = 1 13/16 in. (46 mm)
Dia. = 2 in. (51 mm)

Halogen MR16

- Dichroic reflector
- Constant luminous intensity over lamp life
- Long life 5 000 hours
- UV stop capsule
- Axial filament for improved light distribution

Infrared coating (IRC) offers much higher luminous efficacy. They emit the same amount of light and use up to 30 % less electricity. A 35 watt infrared lamp emits the same light output as a conventional 50 watt lamp and a 50 watt infrared lamp emits the same light output as a conventional 75 watt lamp.

Order code	Description	Watts (W)	Base	Volts (V)	Colour temp. (K)	Average life (hrs)	Beam angle (°)	Beam spread	Center Beam Candle Power (CBCP)	Case qty
MR16 IRC - Cover Glass										
59645	RJLS 14W/12/IRC/SP/GU5.3 (MR16) RAD	14	GU5.3	12	3 000	5 000	10	Spot	2 800	20
59643	RJLS 14W/12/IRC/WFL/GU5.3 (MR16) RAD	14	GU5.3	12	3 000	5 000	36	Wide flood	480	20
10731	RJLS 20W/12/IRC/SP/GU5.3 (MR16) RAD	20	GU5.3	12	3 000	5 000	10	Spot	5 500	20
10732	RJLS 20W/12/IRC/WFL/GU5.3 (MR16) RAD	20	GU5.3	12	3 000	5 000	38	Wide flood	1 000	20
10733	RJLS 20W/12/IRC/VWFL/GU5.3 (MR16) RAD	20	GU5.3	12	3 000	5 000	60	Very wide flood	450	20
10708	RJLS 35W/12/IRC/SP/GU5.3 (MR16) RAD	35	GU5.3	12	3 000	5 000	10	Spot	11 000	20
10709	RJLS 35W/12/IRC/FL/GU5.3 (MR16) RAD	35	GU5.3	12	3 000	5 000	24	Flood	4 100	20
10710	RJLS 35W/12/IRC/WFL/GU5.3 (MR16) RAD	35	GU5.3	12	3 000	5 000	38	Wide flood	2 200	20
10711	RJLS 35W/12/IRC/VWFL/GU5.3 (MR16) RAD	35	GU5.3	12	3 000	5 000	60	Very wide flood	1 050	20
10712	RJLS 50W/12/IRC/SP/GU5.3 (MR16) RAD	50	GU5.3	12	3 000	5 000	10	Spot	15 000	20
10713	RJLS 50W/12/IRC/FL/GU5.3 (MR16) RAD	50	GU5.3	12	3 000	5 000	24	Flood	5 300	20
10714	RJLS 50W/12/IRC/WFL/GU5.3 (MR16) RAD	50	GU5.3	12	3 000	5 000	36	Wide flood	2 850	20
10715	RJLS 50W/12/IRC/VWFL/GU5.3 (MR16) RAD	50	GU5.3	12	3 000	5 000	60	Very wide Flood	1 450	20

Order code	Description	Watts (W)	Base	Volts (V)	Colour temp. (K)	Average life (hrs)	Beam angle (°)	Beam spread	Center Beam Candle Power (CBCP)	Case qty
MR16 Dichroic - Cover Glass										
62589	RJLS 20W/12/MEGA/WFL/GU5.3 (MR16) RAD	20	GU5.3	12	3 000	5 000	36	Wide flood	780	20
62590	RJLS 35W/12/MEGA/FL/GU5.3 (MR16) RAD	35	GU5.3	12	3 000	5 000	24	Flood	3 100	20
62591	RJLS 35W/12/MEGA/WFL/GU5.3 (MR16) RAD	35	GU5.3	12	3 000	5 000	36	Wide flood	1 500	20
62592	RJLS 50W/12/MEGA/SP/GU5.3 (MR16) RAD	50	GU5.3	12	3 000	5 000	10	Spot	12 500	20
62593	RJLS 50W/12/MEGA/FL/GU5.3 (MR16) RAD	50	GU5.3	12	3 000	5 000	24	Flood	4 400	20
62594	RJLS 50W/12/MEGA/WFL/GU5.3 (MR16) RAD	50	GU5.3	12	3 000	5 000	36	Wide flood	2 200	20
62595	RJLS 50W/12/MEGA/VWFL/GU5.3 (MR16) RAD	50	GU5.3	12	3 000	5 000	60	Very wide flood	1 100	20