

Project: _____

Type: _____

Drawn by: _____ Catalogue #: _____

Date: _____

*Individual Spec Sheet***LED REFLECTOR****P30LN****ORDERING INFORMATION**

Order code: 68236
Model number: P30L/S2/12W/27K/40/STD
UPC: 69549015456
Case quantity: 60

PHYSICAL DATA

Dimensions: 4 3/8" x 3 1/16" (111 x 93 mm)
Shape: PAR30LN
Base: E26
Heat sink color: White

PERFORMANCE DATA

Watts (W): 12
Volts (VAC): 120
Colour temperature (K)¹: 2 700
Lumen output (lm)²: 1 050
Lumen per Watts (lm/W): 88
CRI: 90
Life L70 (h)³: 54 000
Beam angle (°): 40
CBCP: 2 117
Power factor: 0.9
Frequency (Hz): 60
Operating temp. range: - 20 °C / - 4 °F to 40 °C / 104 °F


¹ Typical colour temperature range: +/- 5 %² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %³ Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations**COMPATIBLE DIMMERS**

Brand	Dimmer
LEGRAND	H703PTUW, HCL453P
COOPER	DAL06P, SAL06P, SLC03P, AAL06
LEVITON	IPL06, 6674, DSM10-1LZ
LUTRON	DVCL-153P, CTCL-153P, MACL-153P, AYCL-253P, DVCL-253P, DVELV-300P, SELV-300P, NTELV-600

NOTE: The above table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Standard recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation. Some dimmers may require more than one product for stable operation. The maximum number of products is determined by the dimmer wattage rating with LEDs. Be careful, these dimmers have different ratings depending on the product type. Again, refer to the dimmer installation instructions.



DIMENSIONS




CAUTIONS

- Turn power off before inspection, installation, or removal.
- Suitable for use in totally enclosed luminaires.
- Suitable for use in wet locations.
- Do not open – no user serviceable parts inside.
- Use only on 120 VAC, 60Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Compatible with most dimmers.
- For complete dimmer and warranty information visit www.standardpro.com.
- Operating temperature: -20°C / -4°F to 40 °C / 104 °F.
- 5 Years Limited Warranty.

PHOTOMETRIC DATA¹

68236 • P30L/S2/12W/27K/40/STD • 1 227.6 lm

Polar candela distribution



Zonal lumen summary

Zone	Lumens	% Fixture
0-30	1 008.5	82.2
0-40	1 125.6	91.7
0-60	1 199.2	97.7
60-90	28.4	2.3
0-90	1 227.6	100

Illuminance at a distance

	Center beam fc	Beam width
17.0'	9.73	10.6' 10.5'
34.0'	2.43	21.1' 21.1'
51.0'	1.08	31.7' 31.6'
68.0'	0.61	42.2' 42.1'
85.0'	0.39	52.8' 52.7'
102.0'	0.27	63.4' 63.2'

■ Vert. spread: 34.5°
■ Horiz. spread: 34.4°

¹ Complete IES files available on our website.

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: _____

Company: _____

Signature: _____

Date: _____

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions.
 All products are subject to change or may be discontinued any time without notice.