

Project: _____ Type: _____
 Drawn by: _____ Catalogue #: _____ Date: _____

Individual Spec Sheet

L2TLV

TRI-LEVEL MOTION SENSOR LED STRIP

ORDERING INFORMATION

Order code: 68544
Model number: L2TLV-96LS1-Q/40K
UPC: 069549017177
Case quantity: 1
DLC unique ID: S-CDI7U2 (DLC Premium) / PLVWQ8IJ7RRZ (DLC Standard)

PHYSICAL DATA

Length in. (cm): 94 1/8 (239.20)
Lens material: Frosted PMMA
Housing material: 24 gauge white powder painted steel
Mounting: Surface, suspended or row mounted (V-Hooks included in the box)
Sensor: Integrated tri-level microwave (high frequency) motion sensor

PERFORMANCE DATA

Watts (W): 65
Volts (VAC): 120-347
Color temperature (K): 4 000
Lumen output (lm): 8 645
Efficiency (lm/W): 133
CRI: 80+
Life L70 (h): 190 000
Tested LM-80 (h): 9 000
Power factor: 0.90
THD (%): 10
Frequency (Hz): 50/60
Surge protection (kV): 2.5
Input current (A): 0.54-0.19
Operating temp. range: -20°C to 50°C (-4°F to 122°F)

¹ Typical colour temperature range: +/- 5 %.

² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

³ Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations.

ACCESSORIES (order separately)

Order code	Type
68676	Suspension kit - 2 chains (1 m)
68677	Continuous row mounting connector
68680	Replacement lens 96"
68857	Wireguard kit 96"
68681	Remote control for motion sensor



Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/search.

SENSOR ON-OFF DIMMING SETTING OPTIONS

DETECTION AREA

The detection area can be reduced by selecting the combination on the DIP switches to fit precisely each application.

DIP Switch Options: 100% - 75% - 50% - 25%

Remote Control Options: 100% - 75% - 50% - 25%

HOLD TIME

The time period the luminaire remains at 100% illumination after no motion is detected.

DIP Switch Options: 8s - 30s - 1 min - 5 min - 10 min - 15 min - 30 min

Remote Control Options: 8s - 1 min - 5 min - 15 min - 30 min

STANDBY PERIOD

The time period the luminaire remains at a low light output level before it completely switches off in the long absence of motion. When set to Disable mode, the low light is maintained until motion is detected (Bi-Level).

DIP Switch Options: 0s - 1 min - 3 min - 5 min - 10 min - 30 min - +∞ (DISABLE)

Remote Control Options: 0s - 1 min - 5 min - 30 min - +∞ (DISABLE)

Note: "0s" means on/off control;

" +∞ " means bi-level dimming control, luminaire never switches off when daylight sensor is disabled.

STANDBY DIMMING LEVEL

The level of dimmed low light output after the hold time in the long absence of motion.

DIP Switch Options: 10% - 20% - 30% - 40%

Remote Control Options: 10% - 20% - 30% - 40% - 50%

DAYLIGHT SENSOR

The daylight threshold can be captured and configured on the DIP switches to fit a particular application.

DIP Switch Options: 5 lux - 15 lux - 30 lux - 50 lux - 100 lux - 150 lux - +∞ (DISABLE)

Remote Control Options: 5 lux - 15 lux - 50 lux - 150 lux - +∞ (DISABLE)


	1	2
100%	●	●
75%	●	○
50%	○	●
25%	○	○

	3	4	5
8 s	●	●	●
30 s	●	○	●
1 min	○	●	●
5 min	●	○	○
10 min	○	●	○
15 min	○	○	●
30 min	○	○	○

	6	7	8
0 s	●	●	●
1 min	●	○	●
3 min	○	●	●
5 min	●	○	○
10 min	○	●	○
30 min	○	○	●
+ ∞	○	○	○

	1	2
10%	●	●
20%	●	○
30%	○	●
40%	○	○


	3	4	5	6
5 lux	●	●	●	●
15 lux	○	●	●	●
30 lux	●	○	●	●
50 lux	○	○	●	●
100 lux	●	●	○	●
150 lux	●	●	●	○
+ ∞	○	○	○	○



Detection Area: 100%
Hold Time: 30 min
Standby Period: $+\infty$
Standby Dimming: 20%
Daylight Sensor: Disable

Detection Distance	12 m x 8 m (Max.)
Detection Angle – Wall Mounting	150°
Detection Angle – Ceiling Mounting	360°


L2TLV Series		L2STN Series		Watts (W)	Continuous Row Mounting Maximum	
Order code	Model number	Order code	Model number		120 V	347 V
68544	L2TLV-96LS1-Q/40K	68128	L2STN-96LS1-Q/40K	65	6 Luminaires (1 L2TLV + 5 L2STN)	17 Luminaires (1 L2TLV + 16 L2STN)



PHOTOMETRIC DATA¹

68544 • L2TLV-96LS1-Q/40K • 8 638.7 lm

Polar candela distribution

¹ Complete IES files available on our website.

Zonal lumen summary

Zone	Lumens	% Fixture
0-30	1 819.8	21.1%
0-40	2 984.9	34.6%
0-60	5 377.5	62.2%
60-90	2 301.2	26.6%
70-100	1 669.0	19.3%
90-120	755.6	8.7%
0-90	7 678.8	88.9%
90-180	959.9	11.1%
0-180	8 638.7	100%

Illuminance at a distance

Center beam fc		Beam width	
1.7'	812 fc	4.4'	8.5'
3.3'	216 fc	8.6'	16.5'
5.0'	93.9 fc	13.1'	25.0'
6.7'	52.3 fc	17.5'	33.5'
8.3'	34.1 fc	21.7'	41.5'
10.0'	23.5 fc	26.1'	50.0'

Vert. spread: 105.2°
Horiz. spread: 136.4°

Qty

Description

Price

I accept the specifications of the luminaire configuration mentioned above.

Name: _____

Company: _____

Signature: _____

Date: _____

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions.
All products are subject to change or may be discontinued any time without notice.