

Individual Spec Sheet

LPDL CCT SELECTABLE

LOW PROFILE DOWNLIGHT

5 color temperature selection

ORDERING INFORMATION

Order code: 68732
Model number: LPDL4/RND/9W/5CCT/WH/WET
UPC: 069549018754
Case quantity: 24

PHYSICAL DATA

Size in (cm): 4 (10.16)
Shape: Round
Finish: White
Lens type: Frosted Polycarbonate

PERFORMANCE DATA

Watts (W): 9
Volts (V AC): 120
Color temp. (K):¹ 2 700/3 000/3 500/4 000/5 000
Lumen output (lm):² 550
Lumen per Watts (lm/W): 61
CRI: 80+
Life L70 (h):³ 50 000
Beam angle (°): 110
Environment: Wet location
THD (%): <20
Power factor: >0.9
Frequency (Hz): 60
Operating temp. range: -20 °C to 45 °C (-4 °F to 113 °F)
Dimmable: Yes

¹ Typical color temperature range: +/- 5 %.

² Lumen values are derived from Energy Star reported data. Initial lumens range: +/- 10 %.

³ Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations.

COMPATIBLE ACCESSORIES

Order code	Model number	Type
66058	ACC/MPLATE/4.25/ADJ/STD	Adjustable mounting plate
66821	ACC/MPLATE/4.25IN/HANG.BARS/STD	Mounting plate with hanger bars
66051	ACC/MPLATE/4.25/SQR/STD	Square mounting plate
66143	ACC/4/VAPOR BARRIER/STD	Vapor barrier extender
68986 ¹	GOOF RING-4.25IN	Goof rings
64264 ²	LPDL/ACC/6FT/EXTCABLE/STD	6' Extension cord

¹ Please note that the white finish of the goof rings differs from the white finish of the LPDL Stanpro Series.

² Up to 6 FT4 extension cords can be connected together.




COMPATIBLE DIMMERS

Brand	Model
LEVITON	IPL06, 6674, DSL06-1ZL, DSM10-1LZ, IPE04-1LZ, DDMX1
LUTRON	PD-5NE, PD-6WCL, RRD-6NA, DVCL-153P, CTCL-153P, DVCL-253P, AYCL-253P, DVRP-253, SELV-300P, MACL-153P
COOPER	AAL06
LEGRAND	RH703PTUTC

NOTE: The above table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Stanpro recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation. Some dimmers may require more than one product for stable operation. The maximum number of products is determined by the dimmer wattage rating with LEDs. Be careful, these dimmers have different ratings depending on the product type. Again, refer to the dimmer installation instructions.


DIMENSIONS



PHOTOMETRIC DATA¹

68732 • LPDL4/RND/9W/5CCT/WH/WET • 3 000 K • 687.4 lm

Polar candela distribution



¹ Complete IES files available on our website.

Zonal lumen summary

Zone	Lumens	% Fixture
0-30	180.6	28.3
0-40	294.2	46.1
0-60	511.9	80.2
60-90	126.6	19.8
0-90	638.5	100
90-120	2.2	0.3
0-90	683.3	99.4
90-180	4.0	0.6
0-180	687.4	100

Illuminance at a distance

Center beam fc	Beam width
1.7'	87.6
3.3'	23.3
5.0'	10.1
6.7'	5.64
8.3'	3.68
10.0'	2.53

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: _____
 Company: _____
 Signature: _____

Date: _____

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.