

Project:		Type:
,	0.1.1	
Drawn by:	Catalogue #:	Date:

Individual Spec Sheet

LED HIGH OUTPUT LAMP

PS30

ORDERING INFORMATION

68927 Order Code:

PS30/36W/50K/120-277/EX39/STD **Model Number:**

UPC: 069549022539

Case Quantity:

DLC Unique ID: PPNVCTU7

PHYSICAL DATA

Shape: PS30 EX39 Base: **Heat Sink Color:** White Finish: Frosted

PERFORMANCE DATA

Watts (W): 36 Traditional Equivalent (W): 300 Volts (VAC): 120-277 Color Temperature (K)1: 5 000 Lumen Output (Im)2: 4 500 Efficacy (lm/W): 125 80 Life L70 (h)3: 50 000 Beam Angle (°): 270 Power Factor (%): 0.90 Frequency (Hz): 60

Operating Temp. Range: - 30 °C to 40 °C (- 22 °F to 104 °F)

COMPATIBLE DIMMERS¹

Brand	Model
COOPER	AAL06
LEVITON	DDMX1
LUTRON	RRD-6NA-WH, DVCL-153P, DVRP-253-WH, SELV-300P, MACL-153P

Dimming range: 10%-100%

¹This table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Some dimmers may require more than one product for stable operation. Stanpro recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation.



















Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/search.






¹ Typical colour temperature range: +/- 5 %.

² Lumen values are derived from photometric testing, Initial lumens range: +/- 10 %.
3 Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 extrapolations.



DIMENSIONS



Qty	Description	Price	
I accept the specification	ations of the luminaire configuration mentioned above.		
Name:			
Company: Signature:			
Signature:		Date:	

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.