

Project:	Type:		
		7F -	
Drawn by:	Catalogue #:	Date:	

## Individual Spec Sheet

# **LED REFLECTORS**

## **R20**

5 CCT Selectable

### **ORDERING INFORMATION**

Order Code:

**Model Number:** R20/6.5W/5CCT/STD UPC: 069549026872

**Case Quantity:** 

#### **PHYSICAL DATA**

Shape: E26 Base: **Heat Sink Color:** White

#### PERFORMANCE DATA

Watts (W): Volts (VAC): 120

Colour Temperature (K)1: 2 7000/3 000/3 500/4 000/5 000

Lumen Output (Im)2: Efficacy (Im/W): 81 80 CRI: 25 000 Life L70 (h)3: Dimming: Phase cut Beam Angle (°): 105 **Power Factor:** 0.91 Frequency (Hz):

Operating Temp. Range: -20 °C to 45 °C / -4 °F to 113 °F

#### **LUMEN SPECIFICATION TABLE**

2 700 K		3 000 K		3 500 K		4 000 K		5 000 K	
Lumen	Efficacy	Lumen	Efficacy	Lumen	Efficacy	Lumen	Efficacy	Lumen output	Efficacy
(lm)	(Im/W)	(Im)	(Im/W)	(Im)	(Im/W)	(Im)	(Im/W)	(Im)	(Im/W)
631	97	673	103	713	110	715	110	661	102

#### **DEFAULT PROGRAMMING**


2 700 K

#### COMPATIBLE DIMMERS<sup>1</sup>

Brand	Model
LUTRON	PD-5NE, PD-6WCL, DVCL-153P, CTCL-153P, DVCL-253P, DVRP-253-WH, SELV-300P, MACL-153P
COOPER	RRD-6NA-WH, AAL06, SLC03P
LEVITON	IPL06, 6674, DSL06-1ZL, DSM10-1LZ, DDMX1
LEGRAND	RH703PTUTC

<sup>1</sup> This table shows dimmers that have been tested and have demonstrated proper operation under Initiatable shows diminifest that have been tested and nave demonstrateal proper operation under normal conditions. Each installation being unique, various factors such as load, common neutral or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Some dimmers may require more than one product for stable operation. Standard recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation.

#### **DIMENSIONS**

















**ICES** 005











<sup>&</sup>lt;sup>1</sup> Typical colour temperature range: +/- 5 %.

<sup>2</sup> Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

<sup>3</sup> Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 extrapolations.