

Project: \_\_\_\_\_ Type: \_\_\_\_\_  
 Drawn by: \_\_\_\_\_ Catalogue #: \_\_\_\_\_ Date: \_\_\_\_\_

## Individual Spec Sheet

# LED HIGH INTENSITY LAMP

CCT and Power Selectable

### ORDERING INFORMATION

**Order code:** 69421  
**Model number:** CRN/PS120W/3CCT/BYP/120-347/EX39/STD  
**UPC:** 069549027299  
**Case quantity:** 9  
**DLC Unique ID:** S-T3K5LC

### PHYSICAL DATA

**Base:** EX39  
**Type:** 360° High Intensity

### PERFORMANCE DATA

**Watts (W):** 80/100/120  
**Traditional equivalent (W):** 400  
**Volts (V AC):** 120-347  
**Color temperature (K)<sup>1</sup>:** 3 000/4 000/5 000  
**Lumen output (lm)<sup>2</sup>:** 12 000/15 000/18 000  
**Efficacy (lm/W):** 150  
**CRI:** >80  
**Life L70 (h)<sup>3</sup>:** 50 000  
**Dimmable:** No  
**Beam angle (°):** 360  
**Power factor:** >0.9  
**Frequency (Hz):** 50/60  
**Operating temp. range:** - 40 °C / - 40 °F to 45 °C / 113 °F  
**Installation:** Ballast bypass  
**Application (Indoor/Outdoor):** Indoor and Outdoor

<sup>1</sup> Typical color temperature range: +/- 5 %.

<sup>2</sup> Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

<sup>3</sup> Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations.

### DIMENSIONS



**5** yrs  
**warranty**

**6**  
**damp**  
**location**



**ICES**  
**005**



**enclosed**  
**fixture**

**RHS**



**FCC**



This lighting equipment meets requirements of ICES-005 issue 5 class B for use in residential applications.  
 Data is based upon tests performed in a controlled environment.  
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.