

Project: \_\_\_\_\_ Type: \_\_\_\_\_  
 Drawn by: \_\_\_\_\_ Catalogue #: \_\_\_\_\_ Date: \_\_\_\_\_

## Individual Spec Sheet

# LED REFLECTORS CHOICE SERIES

## MR16-GU5.3

### ORDERING INFORMATION

**Order Code:** 69235  
**Model Number:** MR16/S3/12V/6.5W/40K/35/CHOICE/STD  
**UPC:** 069549025660  
**Case Quantity:** 24

### PHYSICAL DATA

**Shape:** MR16  
**Base:** GU5.3  
**Heat Sink Color:** White

### PERFORMANCE DATA


**Watts (W):** 6.5  
**Volts (VAC):** 12  
**Colour Temperature (K):** 4 000  
**Lumen Output (lm):** 518  
**Efficacy (lm/W):** 86  
**CRI:** 80  
**Life L70 (h):** 25 000  
**Dimming:** Phase cut  
**Beam Angle (°):** 35  
**CBCP:** 1 315  
**Power Factor:** 0.90  
**Frequency (Hz):** 60  
**Operating Temp. Range:** - 20 °C to 40 °C / - 4 °F to 104 °F

<sup>1</sup> Typical colour temperature range: +/- 5 %.

<sup>2</sup> Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

<sup>3</sup> Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 extrapolations.

### DIMENSIONS



**3**  
 yrs  
 warranty



dimable

6

damp  
 location



ICES  
 005



This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.  
 Data is based upon tests performed in a controlled environment.  
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.