

Project: _____ Type: _____
 Drawn by: _____ Catalogue #: _____ Date: _____

Individual Spec Sheet

CIELO

3" TRIMLESS LED DOWNLIGHT

5 CCT Selectable Gimbal

ORDERING INFORMATION

Order Code: 70475
Model Number: DLCL3R-12A-5CWH
UPC: 069549035072
Case Quantity: 24

PHYSICAL DATA

Size in (cm): 3 5/8 x 5 1/8 x 5 1/8 (9.1 x 12.9 x 12.9)
Shape: Round
Finish: White
Lens Type: Clear PC
Mounting: Recessed

PERFORMANCE DATA

Watts (W): 12
Volts (V AC): 120
Color Temperature (K)¹: 2 700/3 000/3 500/4 000/5 000
Lumen Output (lm)²: 1 000
Efficacy (lm/W): 83
CRI: 90+
Life L70 (h)³: 50 000
Beam Angle (°): 38
Environment: Wet location
THD (%): <20
Power Factor: >0.9
Cable Rating: FT6
Frequency (Hz): 60
Operating Temp. Range: -30 °C to 45 °C (-22 °F to 113 °F)
Dimmable: Phase cut (ELV / Triac)

¹ Typical color temperature range: +/- 5 %.

² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

³ Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 extrapolations.

LUMEN SPECIFICATION TABLE

Watts (W)	2 700 K		3 000 K		3 500 K		4 000 K		5 000 K	
	Lumen output (lm)	Efficacy (lm/W)	Lumen output (lm)	Efficacy (lm/W)	Lumen output (lm)	Efficacy (lm/W)	Lumen output (lm)	Efficacy (lm/W)	Lumen output (lm)	Efficacy (lm/W)
12	1 128	94	1 170	97	1 217	101	1 234	103	1 200	100

DEFAULT PROGRAMMING

2 700 K


This lighting equipment meets requirements of ICES-005 issue 5 class B for use in residential applications.

Data is based upon tests performed in a controlled environment.

Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.



DIMENSIONS AND WEIGHT



Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: _____

Company: _____

Signature: _____ Date: _____

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice. Please contact your Stanpro customer service representative to confirm inventory levels at time of order.