

KEYSTONE Wall Pack

20W / 30W / 40W | 3000K | 120-347V

Suitable for use in commercial and industrial building projects needing a sleek, customizable luminaire that enhances building aesthetics.

PRODUCT CODES: KWP-40W-3P-3CCT-UD-BK, KWP-40W-3P-3CCT-UD-BZ, KWP-40W-3P-3CCT-UD-WH



Power Selectable

20W / 30W / 40W

120-347V Universal Driver

0-10V dimming

Available in Black (BK),
Bronze (BZ), and White (WH)

Built-in Photocell

unplug to bypass

Type II Optics Standard

Type III and Type IV
Interchangeable Optics
sold separately

Motion Sensor Compatible

sold separately

DarkSky Approved

when set to 3000K operation



TECHNICAL DATA



**DARKSKY
APPROVED**
Reduces light pollution
Certified by DarkSky.org



LIGHT SPECIFICATIONS

Efficacy	152 lm/W
CCT	3000K
CRI	>80
Distribution	Type II
Dimmable	0-10V
L70 Life	50,000 hrs
Warranty	10-year
Factory Settings	40W 4000K

LUMEN OUTPUT	
	3000K
20W	3649 lm
30W	5417 lm
40W	6075 lm


APPROVALS & LISTINGS

cUL	E482965
-----	---------

DIMENSIONS AND WEIGHTS

Fixture Weight	3.7 lbs
Fixture Dimensions	10.65 x 9.36 x 6.85 in
Carton Qty	1
Carton Weight	6.38 lbs
Carton Dimensions	12 x 10.3 x 7.8 in

DIMENSIONAL DRAWINGS (IN)



ELECTRICAL

Wattage	20W/30W/40W
Voltage	120-347V
Current	0.4A
Surge Protection	6kV
Auxiliary Output	12V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 50°C
Operating Temp (with Sensor)	-25 to 50°C

CONSTRUCTION

Housing	Die-Cast Aluminum
Lens	Polycarbonate
Finish	Powder Coated
Finish Colour	Black / Bronze / White
IP Rating	IP65

ACCESSORIES (Sold Separately)

Infrared Motion Sensor	MS01-PIR-TW-DC
Microwave Motion Sensor	MS04-MW-TW-DC
Type III Optics	KWP-TYPE-III-SM
Type IV Optics	KWP-TYPE-IV-SM
Type IV Amber Optics	KWP-TYPE-IV-SM-AM
Motion Sensor Remote	MS04-RC

NOTE: MS04-RC is required for Microwave and Infrared Motion Sensors to function