

Project:		Type:
Drawn by:	Catalogue #:	Date:

Individual Spec Sheet

LOW VOLTAGE LED TAPE

1.5 W, 12 V - IP22

ORDERING INFORMATION

Order code:

Model number: TAPE/16.4'/1.5W/30K/12V/IP22/60/8MM/STD

UPC: 069549658950

Case quantity:



Reel Total Length: 16.4 ft. (5 m) Jacketed or Unjacketed: Unjacketed Wire gauge: 22 AWG

Number of LEDs: 60 LEDs per meter

18 LEDs per foot

Cuttable length: 2 in. (50 mm) or every 3 LED chips

Maximum run length: 33 ft. (10 m)

Operating Temperature: -25°C / -13°F to 40°C / 104°F

PERFORMANCE DATA

Volts (V DC):

3 000 (Neutral white) Color temperature (K): Watts per length: 24 W per reel 4.8 W per meter

0.12 W per inch

Light output per length: 1 800 lm per reel

> 360 lm per meter 9 Im per inch

Efficacy (Im/W): 75 CRI: 90 +Life (hrs): 50 000 120 Beam angle (°):

¹ Typical Color temperature range: +/- 5 % ² Lumen values are derived from photometric testing. Initial lumens range: +/- 5 %

³ Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations

Extrusions, drivers and accessories are available (sold seperatly).

Custom lenghts available upon request. Ask your sales representative for more information.















This lighting equipment complies with Canadian standard ICES-005 for use in residential applications Data is based upon tests performed in a controlled environment.


Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.





DIMENSIONS





Qty		Description	Price		
I accept the specifications of the luminaire configuration mentioned above. Name:					
Company: Signature:			Date:		

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

