

Order code	Description		Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	Initial lumens (lm)	MOL (in.) (mm)	LCL (in.) (mm)	Case qty
A15												
50125	15A15/CL/5M/130V/STD		15	E26	130	Clear	5 000	C-9	90	3.5 89	2.4 61	250
50166	15A15/F/5M/130V/STD		15	E26	130	Frost	5 000	C-9	90	3.5 89	2.4 61	250
50145	25A15/CL/5M/130V/STD		25	E26	130	Clear	5 000	C-9	150	3.5 89	2.4 61	250
50126	25A15/F/5M/130V/STD		25	E26	130	Frost	5 000	C-9	150	3.5 89	2.4 61	250
10328	25A15/SW/5M/130V/STD		25	E26	130	Soft white	5 000	C-9	130	3.5 89	2.4 61	250
52427	30A15/CL/5M/130V/STD		30	E26	130	Clear	5 000	C-9	160	3.5 89	2.4 61	250
50144	40A15/CL/5M/130V/STD		40	E26	130	Clear	5 000	C-9	280	3.5 89	2.4 61	250
50124	40A15/F/5M/130V/STD		40	E26	130	Frost	5 000	C-9	280	3.5 89	2.4 61	250
10329	40A15/SW/5M/130V/STD		40	E26	130	Soft white	5 000	C-9	250	3.5 89	2.4 61	250
50127	60A15/CL/5M/130V/STD		60	E26	130	Clear	5 000	C-9	540	3.5 89	2.4 61	250
50146	60A15/F/5M/130V/STD		60	E26	130	Frost	5 000	C-9	540	3.5 89	2.4 61	250
10330	60A15/SW/5M/130V/STD		60	E26	130	Soft white	5 000	C-9	510	3.5 89	2.4 61	250
A19												
50941	15A19/CL/6M/130V/STD		15	E26	130	Clear	6 000	C-9	105	4.3 108	2.9 73	120
50128	15A19/F/6M/130V/STD		15	E26	130	Frost	6 000	C-9	105	4.3 108	2.9 73	120
50024	25A19/CL/6M/130V/STD/2P	(2 pack)	25	E26	130	Clear	6 000	C-9	168	4.3 108	2.9 73	120
50028	25A19/F/6M/130V/STD/2P	(2 pack)	25	E26	130	Frost	6 000	C-9	168	4.3 108	2.9 73	120
50942	25A19/CL/6M/130V/STD/4P	(4 pack)	25	E26	130	Clear	6 000	C-9	168	4.3 108	2.9 73	120
50943	25A19/F/6M/130V/STD/4P	(4 pack)	25	E26	130	Frost	6 000	C-9	168	4.3 108	2.9 73	120
50025	40A19/CL/6M/130V/STD/2P	(2 pack)	40	E26	130	Clear	6 000	C-9	300	4.3 108	3.1 78	120
50933	40A19/CL/1M/120V/STD/4P	(4 pack)	40	E26	120	Clear	1 000	C-9	495	4.3 108	3.1 78	120
50944	40A19/CL/6M/130V/STD/4P	(4 pack)	40	E26	130	Clear	6 000	C-9	360	4.3 108	3.1 78	120
14629	40A19/F/2M/B22/130V		40	B22	130	Frost	2 000	C-9	300	4.3 108	3.1 78	100
50029	40A19/F/6M/130V/STD/2P	(2 pack)	40	E26	130	Frost	6 000	C-9	300	4.3 108	3.1 78	120
50934	40A19/F/1M/120V/STD/4P	(4 pack)	40	E26	120	Frost	1 000	C-9	495	4.3 108	3.1 78	120
50945	40A19/F/6M/130V/STD/4P	(4 pack)	40	E26	130	Frost	6 000	C-9	300	4.3 108	3.1 78	120
50935	60A19/CL/1M/120V/STD/4P	(4 pack)	60	E26	120	Clear	1 000	C-9	865	4.3 108	3.1 78	120
50946	60A19/CL/6M/130V/STD/4P	(4 pack)	60	E26	130	Clear	6 000	C-9	690	4.3 108	3.1 78	120
50026	60A19/CL/6M/130V/STD/2P	(2 pack)	60	E26	130	Clear	6 000	C-9	630	4.3 108	3.1 78	120
50936	60A19/F/1M/120V/STD/4P	(4 pack)	60	E26	120	Frost	1 000	C-9	865	4.3 108	3.1 78	120
14630	60A19/F/2M/B22/130V		60	B22	130	Frost	2 000	C-9	630	4.3 108	3.1 78	100
50947	60A19/F/6M/130V/STD/4P	(4 pack)	60	E26	130	Frost	6 000	C-9	669	4.3 108	3.1 78	120
50039	60A19/F/6M/130V/STD/2P	(2 pack)	60	E26	130	Frost	6 000	C-9	630	4.3 108	3.1 78	120
*50937	75A19/CL/1M/120V/STD/4P	(4 pack)	75	E26	120	Clear	1 000	C-9	1 210	4.3 108	3.1 78	120
10363	75A19/CL/6M/130V/STD/4P	(4 pack)	75	E26	130	Clear	6 000	C-9	940	4.3 108	3.1 78	120
*50938	75A19/F/1M/120V/STD/4P	(4 pack)	75	E26	120	Frost	1 000	C-9	1 210	4.3 108	3.1 78	120
10362	75A19/F/6M/130V/STD/4P	(4 pack)	75	E26	130	Frost	6 000	C-9	940	4.3 108	3.1 78	120
*50939	100A19/CL/1M/120V/STD/4P	(4 pack)	100	E26	120	Clear	1 000	C-9	1 625	4.3 108	3.1 78	120
*50948	100A19/CL/6M/130V/STD/4P	(4 pack)	100	E26	130	Clear	6 000	C-9	1 340	4.3 108	3.1 78	120
*50027	100A19/CL/6M/130V/STD/2P	(2 pack)	100	E26	130	Clear	6 000	C-9	1 265	4.3 108	3.1 78	120
*50940	100A19/F/1M/120V/STD/4P	(4 pack)	100	E26	120	Frost	1 000	C-9	1 625	4.3 108	3.1 78	120
14631	100A19/F/2M/B22/130V		100	B22	130	Frost	2 000	C-9	1 260	4.3 108	2.4 61	100
*50949	100A19/F/6M/130V/STD/4P	(4 pack)	100	E26	130	Frost	6 000	C-9	1 265	4.3 108	3.1 78	120
*50040	100A19/F/6M/130V/STD/2P	(2 pack)	100	E26	130	Frost	6 000	C-9	1 265	4.3 108	3.1 78	120
A21												
50116	100A21/CL/5M/130V/STD		100	E26	130	Clear	5 000	C-9	1 030	5.3 135	3.5 89	120
50515	100A21/F/5M/130V/STD		100	E26	130	Frost	5 000	C-9	1 030	5.3 135	3.5 89	120

* Not for sale in British Columbia as per BC Energy Efficiency Act Standards on General Service Lighting.

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	Initial lumens (lm)	MOL (in.) (mm)		LCL (in.) (mm)		Case qty
A21 (Cont.)													
*50085	150A21/CL/5M/130V/STD	150	E26	130	Clear	5000	C-9	1650	5.3	135	3.5	89	120
*50481	150A21/F/5M/120V/STD	150	E26	120	Frost	5000	C-9	1700	5.3	135	3.5	89	120
*50067	150A21/F/5M/130V/STD	150	E26	130	Frost	5000	C-9	1650	5.3	135	3.5	89	120
A23													
50163	100A23/CL/5M/130V/STD	100	E26	130	Clear	5000	C-9	1000	6.2	157	5.0	127	60
50069	100A23/F/5M/130V/STD	100	E26	130	Frost	5000	C-9	1000	6.2	157	5.0	127	60
*50142	150A23/CL/5M/130V/STD	150	E26	130	Clear	5000	C-9	1650	6.2	157	5.0	127	60
*50070	150A23/F/5M/130V/STD	150	E26	130	Frost	5000	C-9	1650	6.2	157	5.0	127	60
*50086	200A23/CL/5M/130V/STD	200	E26	130	Clear	5000	C-9	2400	6.2	157	5.0	127	60
*50068	200A23/F/5M/130V/STD	200	E26	130	Frost	5000	C-9	2400	6.2	157	5.0	127	60
B4													
14683	3B4/CL/E10/14V	3	E10	14	Clear	2500	C-6	12	1.7	43	N/A	N/A	100
B8													
50635	15B8/CL/2.5M/E12/130V/STD	15	E12	130	Clear	2500	C-7A	90	3.2	80	1.8	45	500
50638	15B8/F/2.5M/E12/130V/STD	15	E12	130	Frost	2500	C-7A	88	3.2	80	1.8	45	500
50636	25B8/CL/2.5M/E12/130V/STD	25	E12	130	Clear	2500	CC-2V	200	3.2	80	1.9	47	500
50639	25B8/F/2.5M/E12/130V/STD	25	E12	130	Frost	2500	C-7A	150	3.2	80	1.8	45	500
50637	40B8/CL/2.5M/E12/130V/STD	40	E12	130	Clear	2500	CC-2V	310	3.2	80	1.9	47	500
50640	40B8/F/2.5M/E12/130V/STD	40	E12	130	Frost	2500	CC-2V	300	3.2	80	1.9	47	500
50645	60B8/CL/2.5M/E12/130V/STD	60	E12	130	Clear	2500	CC-2V	600	3.2	80	1.9	47	500
B10													
50611	15B10/CL/3M/E12/130V/STD	15	E12	130	Clear	3000	C-7A	90	3.9	99	1.8	45	500
50632	15B10/CL/3M/130V/STD	15	E26	130	Clear	3000	C-7A	90	3.5	89	2.1	54	500
10499	15B10/F/3M/130V/STD	15	E26	130	Frost	3000	C-7A	85	3.9	99	1.8	45	500
50543	25B10/CL/3M/E12/130V/STD	25	E12	130	Clear	3000	C-7A	155	3.9	99	1.8	45	500
50612	25B10/F/3M/E12/130V/STD	25	E12	130	Frost	3000	CC-2V	150	3.9	99	1.9	47	500
50548	25B10/CL/3M/E14/130V/STD	25	E14	130	Clear	3000	C-7A	155	4.0	101	2.1	54	500
50551	25B10/F/3M/E14/130V/STD	25	E14	130	Frost	3000	C-7A	150	4.0	101	2.1	54	500
50621	25B10/CL/3M/130V/STD	25	E26	130	Clear	3000	C-7A	155	3.5	89	2.1	54	500
50624	25B10/F/3M/130V/STD	25	E26	130	Frost	3000	C-7A	150	3.5	89	2.1	54	500
50544	40B10/CL/3M/E12/130V/STD	40	E12	130	Clear	3000	C-7A	300	3.9	99	1.8	45	500
50613	40B10/F/3M/E12/130V/STD	40	E12	130	Frost	3000	CC-2V	280	3.9	99	1.9	47	500
52150	40B10/WH/3M/E12/130V/STD	40	E12	130	White	3000	C-7A	280	3.7	95	1.9	47	500
50549	40B10/CL/3M/E14/130V/STD	40	E14	130	Clear	3000	CC-2V	300	4.0	101	1.9	47	500
50552	40B10/F/3M/E14/130V/STD	40	E14	130	Frost	3000	C-7A	270	4.0	101	2.1	54	500
50622	40B10/CL/3M/130V/STD	40	E26	130	Clear	3000	C-7A	280	3.5	89	2.1	54	500
50625	40B10/F/3M/130V/STD	40	E26	130	Frost	3000	C-7A	270	3.5	89	2.1	54	500
B10 (Suitable for use base up)													
50545	60B10/CL/3M/E12/130V/STD	60	E12	130	Clear	3000	C-7A/3	550	3.9	99	2.0	52	500
50614	60B10/F/3M/E12/130V/STD	60	E12	130	Frost	3000	C-7A/3	540	4.0	101	2.1	54	500
50550	60B10/CL/3M/E14/130V/STD	60	E14	130	Clear	3000	C-7A/3	550	3.9	99	2.0	52	500
50553	60B10/F/3M/E14/130V/STD	60	E14	130	Frost	3000	C-7A/3	540	4.0	101	2.1	54	500
50623	60B10/CL/3M/130V/STD	60	E26	130	Clear	3000	C-7A/3	550	3.9	99	2.1	54	500
50626	60B10/F/3M/130V/STD	60	E26	130	Frost	3000	C-7A/3	540	3.9	99	2.1	54	500

* Not for sale in British Columbia as per BC Energy Efficiency Act Standards on General Service Lighting.

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	Initial lumens (lm)	MOL (in.) (mm)	LCL (in.) (mm)	Case qty
BR30											
50219	50BR30/FL/5M/130V/STD	50	E26	130	Clear	5000	C-9	340	5.1 130	3.3 84	60
¹ 50220	60BR30/FL/5M/130V/STD	60	E26	130	Clear	5000	C-9	420	5.1 130	3.3 84	60
BR30 (Energy Saver)											
50079	65BR30/SP/5M/ES/130V/STD	65	E26	130	Clear	5000	CC-6	510	5.1 130	3.3 84	60
50077	65BR30/FL/5M/ES/130V/STD	65	E26	130	Clear	5000	CC-6	510	5.1 130	3.3 84	60
¹ 52000	85BR30/FL/5M/ES/130V/STD	85	E26	130	Clear	5000	CC-6	700	5.1 130	3.3 84	24
BR38											
¹ 50055	75BR38/FL/5M/130V/STD	75	E26	130	Clear	5000	C-9	650	5.8 147	3.3 84	12
¹ 50056	75BR38/SP/5M/130V/STD	75	E26	130	Clear	5000	C-9	765	5.8 147	3.3 84	12
¹ 50053	100BR38/FL/5M/130V/STD	100	E26	130	Clear	5000	C-9	980	5.8 147	3.3 84	12
¹ 14703	100BR38/SP/5M/130V	100	E26	130	Clear	5000	C-9	980	5.8 147	3.3 84	12
BR38 (Energy Saver)											
¹ 52105	120BR38/SP/5M/ES/130V/STD	120	E26	130	Clear	5000	CC-6	1180	5.8 147	3.3 84	12
¹ 52001	120BR38/FL/5M/ES/130V/STD	120	E26	130	Clear	5000	CC-6	1180	5.8 147	3.3 84	12
BR40											
¹ 50062	75BR40/FL/5M/130VSTD	75	E26	130	Clear	5000	C-9	630	6.6 167	4.3 108	24
¹ 50064	100BR40/FL/5M/130V/STD	100	E26	130	Clear	5000	C-9	930	6.6 167	4.3 108	24
¹ 50483	200BR40/FL/5M/130V/STD	200	E26	130	Clear	5000	C-9	2050	6.6 167	4.4 111	24
50482	300BR40/FL/5M/130V/STD	300	E26	130	Clear	5000	C-9	3000	6.6 167	4.3 108	24
BR40 (Energy Saver)											
50080	65BR40/FL/5M/ES/130V/STD	65	E26	130	Clear	5000	CC-6	520	6.6 167	4.3 108	24
¹ 50081	85BR40/FL/5M/ES/130V/STD	85	E26	130	Clear	5000	CC-6	760	6.6 167	4.3 108	24
¹ 50083	120BR40/SP/5M/ES/130V/STD	120	E26	130	Clear	5000	CC-6	1180	6.6 167	4.3 108	24
C7											
50967	4C7/CL/3M/E12/125V/STD	4	E12	125	Clear	3000	C-7A	15	2.1 54	1.5 38	500
14686	5C7/CL/3M/E12/120V	5	E12	120	Clear	3000	C-7A	20	2.1 54	1.5 38	2000
22008	7C7/CL/2M/E12/120V/STD/2P (2 pack)	7	E12	120	Clear	2000	C-7A	26	2.1 54	1.5 38	120
CA4.5											
50634	7.5CA4.5/CL/2M/E12/120V/STD	7.5	E12	120	Clear	2000	C-7A	45	2.8 70	1.6 41	500
50633	7.5CA4.5/CL/2M/E12/130V/STD	7.5	E12	130	Clear	2000	C-7A	36	2.8 70	1.6 41	500
52154	7.5CA4.5/F/2M/E12/130V/STD	7.5	E12	130	Frost	2000	C-7A	34	2.8 70	1.6 41	500
52153	10CA4.5/CL/2M/E12/130V/STD	10	E12	130	Clear	2000	C-7A	51	2.8 70	1.6 41	500
CA8											
52155	10CA8/CL/2.5M/E12/130V/STD	10	E12	130	Clear	2500	C-7A	65	3.5 89	1.6 41	500
52157	10CA8/F/2.5M/E12/130V/STD	10	E12	130	Frost	2500	C-7A	65	3.5 89	1.6 41	500
50641	15CA8/CL/2.5M/E12/130V/STD	15	E12	130	Clear	2500	C-7A	90	3.6 91	1.8 45	500
10269	15CA8/F/2.5M/E12/130V/STD	15	E12	130	Frost	2500	C-7A	88	3.6 91	1.8 45	120
52156	25CA8/CL/2.5M/E12/130V/STD	25	E12	130	Clear	2500	C-7A	155	3.5 89	1.6 41	120
50643	25CA8/F/2.5M/E12/130V/STD	25	E12	130	Frost	2500	C-7A	150	3.6 91	1.8 45	500
50642	40CA8/CL/2.5M/E12/130V/STD	40	E12	130	Clear	2500	C-7A	280	3.6 91	1.8 45	500
50644	40CA8/F/2.5M/E12/130V/STD	40	E12	130	Frost	2500	C-7A	280	3.6 91	1.8 45	500
CA10											
50615	25CA10/CL/3M/E12/130V/STD	25	E12	130	Clear	3000	CC-2V	180	4.1 104	1.9 47	500
50618	25CA10/F/3M/E12/130V/STD	25	E12	130	Frost	3000	CC-2V	150	4.1 104	1.9 47	500
51051	25CA10/CL/3M/130V/STD	25	E26	130	Clear	3000	C-7A	155	3.9 99	2.1 54	120

¹ This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	Initial lumens (lm)	MOL (in.) (mm)	LCL (in.) (mm)	Case qty
CA10 (Cont.)											
50629	25CA10/F/3M/130V/STD	25	E26	130	Frost	3 000	C-7A	150	3.9 99	2.1 54	500
50616	40CA10/CL/3M/E12/130V/STD	40	E12	130	Clear	3 000	CC-2V	310	4.1 104	1.9 47	500
50619	40CA10/F/3M/E12/130V/STD	40	E12	130	Frost	3 000	C-7A	270	4.1 104	1.9 47	500
50627	40CA10/CL/3M/130V/STD	40	E26	130	Clear	3 000	C-7A	280	3.9 99	2.1 54	500
50630	40CA10/F/3M/130V/STD	40	E26	130	Frost	3 000	C-7A	270	3.9 99	2.1 54	120
50617	60CA10/CL/3M/E12/130V/STD	60	E12	130	Clear	3 000	CC-2V	600	4.1 104	1.9 47	500
50620	60CA10/F/3M/E12/130V/STD	60	E12	130	Frost	3 000	CC-2V	590	4.1 104	1.9 47	500
50628	60CA10/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-7A	600	3.9 99	2.1 54	500
50631	60CA10/F/3M/130V/STD	60	E26	130	Frost	3 000	C-7A	590	3.9 99	2.1 54	500
ER30											
52017	50ER30/FL/5M/130V/STD	50	E26	130	Clear	5 000	C-9	350	6.2 157	4.1 104	60
ER40											
¹ 52018	120ER40/FL/5M/130V/STD	120	E26	130	Clear	5 000	C-9	1 200	7.4 187	5.1 130	24
F10											
14457	15F10/CL/2.5M/E12/130V	15	E12	130	Clear	2 500	C-7A	105	3.1 78	1.7 43	250
F15											
50751	25F15/CL/1.5M/130V/STD	25	E26	130	Clear	1 500	CC-2V	240	4.3 108	2.6 65	500
50750	40F15/CL/1.5M/130V/STD	40	E26	130	Clear	1 500	CC-2V	430	4.3 108	2.6 65	500
50752	60F15/CL/1.5M/130V/STD	60	E26	130	Clear	1 500	CC-2V	680	4.3 108	2.6 65	500
G8											
52164	5G8/CL/1M/E12/130V/STD	5	E12	130	Clear	1 000	C-7A	50	1.9 47	1.3 33	500
G9.5											
52165	7.5G9.5/CL/1M/E12/130V/STD	7.5	E12	130	Clear	1 000	C-7A	50	2.0 52	1.5 38	500
G11											
50759	7.5G11/CL/1M/E12/130V/STD	7.5	E12	130	Clear	1 000	C-5	50	2.3 59	1.5 38	500
50761	7.5G11/CL/1M/130V/STD	7.5	E26	130	Clear	1 000	C-5	50	2.3 59	1.6 41	500
G13											
50681	10G13/CL/3M/E12/130V/STD	10	E12	130	Clear	3 000	C-7A	65	2.4 61	1.7 43	500
50682	25G13/CL/3M/E12/130V/STD	25	E12	130	Clear	3 000	CC-2V	180	2.4 61	1.6 41	500
50773	25G13/F/3M/E12/130V/STD	25	E12	130	Frost	3 000	C-7A	155	2.4 61	1.7 43	500
14786	25G13/IF/MED/115V	25	E26	115	Frost	3 000	C-7A	155	2.4 61	1.7 43	25
50683	40G13/CL/3M/E12/130V/STD	40	E12	130	Clear	3 000	CC-2V	330	2.4 61	1.6 41	500
50775	40G13/F/3M/E12/130V/STD	40	E12	130	Frost	3 000	C-7A	300	2.4 61	1.7 43	500
50684	60G13/CL/3M/E12/130V/STD	60	E12	130	Clear	3 000	C-7A	650	2.4 61	1.7 43	500
G16.5											
10334	5G16.5/CL/3M/E12/130V/STD	5	E12	130	Clear	3 000	C-7A	25	3.0 76	1.9 47	500
10268	10G16.5/CL/3M/E12/130V/STD	10	E12	130	Clear	3 000	C-7A	65	3.0 76	1.9 47	500
50660	15G16.5/CL/3M/E12/130V/STD	15	E12	130	Clear	3 000	C-7A	90	3.0 76	1.9 47	500
50662	15G16.5/WH/3M/E12/130V/STD	15	E12	130	White	3 000	C-7A	80	3.0 76	1.9 47	500
50661	15G16.5/CL/3M/130V/STD	15	E26	130	Clear	3 000	C-7A	90	3.0 76	1.9 47	500
50648	25G16.5/CL/3M/E12/130V/STD	25	E12	130	Clear	3 000	CC-2V	180	3.0 76	1.9 47	500
52161	25G16.5/F/3M/E12/130V/STD	25	E12	130	Frost	3 000	C-7A	155	2.9 73	1.9 47	500
50652	25G16.5/WH/3M/E12/130V/STD	25	E12	130	White	3 000	CC-2V	160	3.0 76	1.9 47	500
50777	25G16.5/CL/3M/E14/130V/STD	25	E14	130	Clear	3 000	CC-6	212	2.9 73	2.0 52	500
50779	25G16.5/WH/3M/E14/130V/STD	25	E14	130	White	3 000	CC-6	200	2.9 73	2.0 52	500
50649	25G16.5/CL/3M/130V/STD	25	E26	130	Clear	3 000	CC-2V	180	3.0 76	1.9 47	500

¹ This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	Initial lumens (lm)	MOL (in.) (mm)		LCL (in.) (mm)		Case qty
G16.5 (Cont.)													
50653	25G16.5/WH/3M/130V/STD	25	E26	130	White	3 000	CC-2V	160	3.0	76	1.9	47	500
50650	40G16.5/CL/3M/E12/130V/STD	40	E12	130	Clear	3 000	CC-2V	330	3.0	76	1.9	47	500
50654	40G16.5/WH/3M/E12/130V/STD	40	E12	130	White	3 000	CC-2V	300	3.0	76	1.9	47	500
50778	40G16.5/CL/3M/E14/130V/STD	40	E14	130	Clear	3 000	CC-6	412	2.9	73	2.0	52	500
50780	40G16.5/WH/3M/E14/130V/STD	40	E14	130	White	3 000	CC-6	387	2.9	73	2.0	52	500
50651	40G16.5/CL/3M/130V/STD	40	E26	130	Clear	3 000	CC-2V	330	3.0	76	1.9	47	500
50655	40G16.5/WH/3M/130V/STD	40	E26	130	White	3 000	CC-2V	300	3.0	76	1.9	47	500
50656	60G16.5/CL/3M/E12/130V/STD	60	E12	130	Clear	3 000	CC-2V	580	3.0	76	1.9	47	500
50658	60G16.5/WH/3M/E12/130V/STD	60	E12	130	White	3 000	CC-2V	525	3.0	76	1.9	47	500
50782	60G16.5/WH/3M/E14/130V/STD	60	E14	130	White	3 000	CC-6	768	2.9	73	2.0	52	500
50657	60G16.5/CL/3M/130V/STD	60	E26	130	Clear	3 000	CC-2V	580	3.0	76	1.9	47	500
50659	60G16.5/WH/3M/130V/STD	60	E26	130	White	3 000	CC-2V	525	3.0	76	1.9	47	500
G19													
14497	25G19/WH/3M/125V	25	E26	125	White	3 000	C-9	160	3.5	89	2.6	65	250
14499	40G19/WH/3M/125V	40	E26	125	White	3 000	C-9	325	3.5	89	2.6	65	250
14500	60G19/CL/3M/125V	60	E26	125	Clear	3 000	C-9	550	3.5	89	2.6	65	250
14501	60G19/WH/3M/125V	60	E26	125	White	3 000	C-9	550	3.5	89	1.6	41	250
G25													
50199	25G25/CL/3M/130V/STD	25	E26	130	Clear	3 000	C-9	150	4.5	114	3.0	76	150
50196	25G25/WH/3M/130V/STD	25	E26	130	White	3 000	C-9	130	4.5	114	3.0	76	150
50222	40G25/CL/3M/130V/STD	40	E26	130	Clear	3 000	C-9	300	4.5	114	3.0	76	150
50155	40G25/WH/3M/130V/STD	40	E26	130	White	3 000	C-9	280	4.5	114	3.0	76	150
50154	60G25/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-9	520	4.5	114	3.0	76	150
50197	60G25/WH/3M/130V/STD	60	E26	130	White	3 000	C-9	480	4.5	114	3.0	76	150
50200	100G25/CL/3M/130V/STD	100	E26	130	Clear	3 000	C-9	1000	4.5	114	3.0	76	150
50198	100G25/WH/3M/130V/STD	100	E26	130	White	3 000	C-9	950	4.5	114	3.0	76	150
G30													
50203	25G30/CL/3M/130V/STD	25	E26	130	Clear	3 000	C-9	150	5.4	137	3.3	84	100
50201	25G30/WH/3M/130V/STD	25	E26	130	White	3 000	C-9	130	5.4	137	3.3	84	100
50204	40G30/CL/3M/130V/STD	40	E26	130	Clear	3 000	C-9	300	5.4	137	3.3	84	100
50202	40G30/WH/3M/130V/STD	40	E26	130	White	3 000	C-9	280	5.4	137	3.3	84	100
50109	60G30/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-9	520	5.4	137	3.3	84	100
50110	60G30/WH/3M/130V/STD	60	E26	130	White	3 000	C-9	480	5.4	137	3.3	84	100
*50156	100G30/CL/3M/130V/STD	100	E26	130	Clear	3 000	C-9	1 140	5.4	137	3.3	84	100
*50157	100G30/WH/3M/130V/STD	100	E26	130	White	3 000	C-9	1 080	5.4	137	3.3	84	100
G40													
50205	25G40/CL/3M/130V/STD	25	E26	130	Clear	3 000	C-9	130	6.9	176	3.9	99	24
50209	25G40/WH/3M/130V/STD	25	E26	130	White	3 000	C-9	130	6.9	176	3.9	99	24
50206	40G40/CL/3M/130V/STD	40	E26	130	Clear	3 000	C-9	300	6.9	176	3.9	99	24
50150	40G40/WH/3M/130V/STD	40	E26	130	White	3 000	C-9	280	6.9	176	3.9	99	24
50111	60G40/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-9	610	6.9	176	3.9	99	24
50158	60G40/WH/3M/130V/STD	60	E26	130	White	3 000	C-9	480	6.9	176	3.9	99	24
50207	100G40/CL/3M/130V/STD	100	E26	130	Clear	3 000	C-9	1 000	6.9	176	3.9	99	24
50210	100G40/WH/3M/130V/STD	100	E26	130	White	3 000	C-9	1 080	6.9	176	3.9	99	24
50208	150G40/CL/3M/130V/STD	150	E26	130	Clear	3 000	C-9	1 550	6.9	176	3.9	99	24
50112	150G40/WH/3M/130V/STD	150	E26	130	White	3 000	C-9	1 550	6.9	176	3.9	99	24

*Not for sale in British Columbia as per BC Energy Efficiency Act Standards on General Service Lighting.

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	Initial lumens (lm)	MOL (in.) (mm)		LCL (in.) (mm)		Case qty
PAR38													
14675	75PAR38/SP/2M/MSP/120V	75	Med side prong	120	Clear	2000	CC-6	750	4.3	108	N/A	N/A	12
17682	75PAR38/FL/2M/MSP/120V	75	Med side prong	120	Clear	2000	CC-6	750	4.3	108	N/A	N/A	12
PAR46 (ST : Screw Terminal)													
14678	25PAR46/CL/1M/ST/5.5V	25	ST G53	5.5	Clear	1000	C-6	140	3.7	95	N/A	N/A	12
14679	150PAR46/1M/ST/130V	150	ST G53	130	Clear	1000	C-13	20000	3.9	99	N/A	N/A	12
14677	200PAR46/NSP/2M/MSP/120V	200	Med side prong	120	Clear	2000	CC-13	2250	4.0	101	N/A	N/A	12
14676	200PAR46/MFL/2M/MSP/120V	200	Med side prong	120	Clear	2000	CC-13	2250	4.0	101	N/A	N/A	12
PAR56													
14680	200PAR56/ST/30V	200	ST* G53	30	Clear	350	CC-8	22000	4.5	114	N/A	N/A	12
PS25													
*50140	150PS25/CL/5M/130V/STD	150	E26	130	Clear	5000	C-9	1600	6.9	176	5.0	127	60
*50141	150PS25/F/5M/130V/STD	150	E26	130	Frost	5000	C-9	1600	6.9	176	5.0	127	60
*50089	200PS25/CL/5M/130V/STD	200	E26	130	Clear	5000	C-9	2400	6.9	176	5.0	127	60
*50072	200PS25/F/5M/130V/STD	200	E26	130	Frost	5000	C-9	2400	6.9	176	5.0	127	60
50071	300PS25/CL/5M/130V/STD	300	E26	130	Clear	5000	C-9	3600	6.9	176	5.0	127	60
50088	300PS25/F/5M/130V/STD	300	E26	130	Frost	5000	C-9	3600	6.9	176	5.0	127	60
PS30													
52428	300PS30/CL/120V/STD	300	E26	120	Clear	5000	C-9	3600	8.1	205	5.4	137	60
51122	300PS30/F/5M/130V/STD	300	E26	130	Frost	5000	C-9	3600	8.1	205	5.4	137	60
PS35													
50225	300PS35/CL/5M/E39/130V/STD	300	E39	130	Clear	5000	C-9	3600	9.4	239	6.5	165	24
50226	300PS35/F/5M/E39/130V/STD	300	E39	130	Frost	5000	C-9	3600	9.4	239	6.5	165	24
50227	500PS35/CL/5M/E39/130V/STD	500	E39	130	Clear	5000	C-9	8000	9.4	239	6.5	165	24
50228	500PS35/F/5M/E39/130V/STD	500	E39	130	Frost	5000	C-9	8000	9.4	239	6.5	165	24
PS52													
14643	750PS52/CL/1M/E39/120 130V	750	E39	120	Clear	1000	C-7A	17040	13.0	330	9.5	241	12
14644	1000PS52/F/1M/E39/120 130V	1000	E39	120	Frost	1000	CC-8	23100	13.0	330	9.5	241	12
R14													
50666	25R14/FL/1.5M/E17/120V/STD	25	E17	120	Clear	1500	CC-2V	160	2.6	65	2.0	52	500
50665	25R14/FL/1.5M/120V/STD	25	E26	120	Clear	1500	CC-2V	160	2.1	54	1.7	43	500
50664	40R14/CL/FL/1.5M/E17/120V/STD	40	E17	120	Clear	1500	CC-2V	300	2.6	65	2.0	52	500
50663	40R14/CL/FL/1.5M/120V/STD	40	E26	120	Clear	1500	CC-2V	420	2.1	54	1.7	43	500
R16													
14816	40R50mm E14 110V	40	E14	110	Frost	1000	CC-2F	330	3.3	84	N/A	N/A	25
50134	40R16/SW/1M/120V/STD	40	E26	120	Soft white	1000	CC-6	472	3.5	89	N/A	N/A	120
50135	60R16/SW/1M/125 130V/STD	60	E26	125	Soft white	1000	CC-6	770	3.5	89	N/A	N/A	120
R19													
50136	40R19/SW/1.5M/120V/STD	40	E26	120	Soft white	1500	CC-6	400	4.0	101	3.0	76	200
¹ 50137	60R19/SW/1.5M/120V/STD	60	E26	120	Soft white	1500	CC-6	700	4.0	101	3.0	76	200
¹ 50138	75R19/SW/1.5M/120V/STD	75	E26	120	Soft white	1500	CC-6	1000	4.0	101	3.0	76	200

¹This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

*Not for sale in British Columbia as per BC Energy Efficiency Act Standards on General Service Lighting.

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	Initial lumens (lm)	MOL (in.) (mm)		LCL (in.) (mm)		Case qty
R20													
50211	30R20/SP/5M/130V/STD	30	E26	130	Clear	5000	C-9	145	3.9	99	3.0	76	200
50215	30R20/FL/5M/130V/STD	30	E26	130	Frost	5000	C-9	135	3.9	99	3.0	76	200
61703	45R20/FL/5M/130V/STD	45	E26	130	Frost	5000	CC-6	242	3.9	100	2.9	75	60
61705	45R20/SP/5M/130V/STD	45	E26	130	Frost	5000	CC-6	254	3.9	100	2.9	75	60
150162	50R20/SP/5M/130V/STD	50	E26	130	Clear	5000	CC-6	310	3.9	99	3.0	76	200
150161	50R20/FL/5M/130V/STD	50	E26	130	Frost	5000	CC-6	280	3.9	99	3.0	76	200
150216	60R20/FL/5M/130V/STD	60	E26	130	Frost	5000	C-9/5	430	3.9	99	3.0	76	200
150217	75R20/FL/5M/130V/STD	75	E26	130	Frost	5000	C-9/5	540	3.9	99	3.0	76	200
150213	75R20/SP/5M/130V/STD	75	E26	130	Clear	5000	CC-6	760	3.9	99	2.6	65	200
R52													
14580	500R52/F/2M/E39/120 130V	500	E39	120	Frost	2000	C7-A	7600	11.7	298	N/A	N/A	12
S11													
50789	5S11/CL/1M/E17/130V/STD	5	E17	130	Clear	1000	C-7A	32	2.3	59	1.5	38	500
50788	5S11/F/1M/E17/130V/STD	5	E17	130	Frost	1000	C-7A	30	2.3	59	1.5	38	500
50143	10S11/CL/1M/E17/130V/STD	10	E17	130	Clear	1000	C-7A	75	1.9	47	2.5	63	500
50165	10S11/F/1M/E17/130V/STD	10	E17	130	Frost	1000	C-7A	75	1.9	47	2.5	63	500
50790	15S11/CL/1M/BA15d/75V/STD	15	BA15d	75	Clear	1000	C-7A	140	2.3	59	1.5	38	500
50787	15S11/CL/1M/E17/130V/STD	15	E17	130	Clear	1000	C-7A	80	2.3	59	1.5	38	500
50786	25S11/CL/1M/E17/130V/STD	25	E17	130	Clear	1000	C-7A	170	2.3	59	1.5	38	500
50791	30S11/CL/BA15d/75V/STD	30	BA15d	75	Clear	1000	C-7A	280	2.3	59	1.5	38	500
50785	30S11/CL/1M/E17/130V/STD	30	E17	130	Clear	1000	C-7A	320	2.3	59	1.5	38	500
50784	30S11/F/1M/E17/130V/STD	30	E17	130	Frost	1000	C-7A	310	2.3	59	1.5	38	500
50123	40S11/CL/1M/E17/130V/STD	40	E17	130	Clear	1000	CC-2V	360	1.9	47	2.5	63	500
50783	40S11/F/1M/E17/130V/STD	40	E17	130	Frost	1000	C-7A	390	2.3	59	1.6	41	500
S14													
50147	11S14/CL/3M/130V/STD	11	E26	130	Clear	3000	C-9	72	3.3	84	2.5	63	500
59542	11S14/CL/8M/130V/STD	11	E26	130	Clear	8000	C-9	55	3.5	89	2.5	63	24
10158	11S14/F/3M/130V/STD	11	E26	130	Frost	3000	C-9	68	3.3	84	2.5	63	500
T4													
14753	15T4/E12/130V	15	E12	130	Clear	1500	C7-A	105	1.9	47	N/A	N/A	10
T6 (Exit Sign)													
50667	15T6/CL/5M/E12/130V/STD	15	E12	130	Clear	5000	C-7A	105	3.0	76	1.6	41	1000
50668	15T6/CL/7.5M/E12/145V/STD	15	E12	145	Clear	7500	C-7A	110	3.0	76	1.6	41	1000
50675	15T6/CL/5M/E17/130V/STD	15	E17	130	Clear	5000	C-7A	105	3.0	76	1.6	41	1000
50676	15T6/CL/7.5M/E17/145V/STD	15	E17	145	Clear	7500	C-7A	110	3.0	76	1.6	41	1000
T6.5 (Energy Saver - Exit Sign)													
52127	7T6.5/CL/40M/ES/E12/145V/STD	7	E12	145	Clear	40000	D	40	5.5	140	5.1	130	500
52128	7T6.5/CL/40M/ES/E17/145V/STD	7	E17	145	Clear	40000	D	40	5.5	140	4.9	125	500
T6.5 (Exit Sign)													
51052	20T6.5/CL/5M/BA15d/130V/STD	20	BA15d	130	Clear	5000	C-8	90	5.5	140	3.0	76	500
50679	20T6.5/F/5M/BA15D/130V/STD	20	BA15d	130	Frost	5000	C-8	90	5.5	140	3.0	76	500
50677	20T6.5/CL/5M/E17/130V/STD	20	E17	130	Clear	5000	C-8	150	5.5	140	3.1	78	120
50678	20T6.5/F/5M/E17/130V/STD	20	E17	130	Frost	5000	C-8	90	5.5	140	3.1	78	500
51056	25T6.5/CL/5M/BA15d/125V/STD	25	BA15d	125	Clear	5000	C-8	170	5.6	142	3.3	84	500

¹This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	Initial lumens (lm)	MOL (in.) (mm)	LCL (in.) (mm)	Case qty
T6.5 (Exit Sign, cont.)											
50674	25T6.5/CL/7.5M/BA15d/145V/STD	25	BA15d	145	Clear	7 500	C-8	150	5.6 142	3.3 84	500
50729	25T6.5/F/7.5M/BA15d/145V/STD	25	BA15d	145	Frost	7 500	C-8	145	5.6 142	3.3 84	500
50671	25T6.5/CL/5M/E12/130V/STD	25	E12	130	Clear	5 000	C-8	170	5.5 140	3.3 84	500
50672	25T6.5/CL/7.5M/E12/145V/STD	25	E12	145	Clear	7 500	C-8	150	5.5 140	3.3 84	500
50669	25T6.5/CL/5M/E17/130V/STD	25	E17	130	Clear	5 000	C-8	170	5.5 140	3.3 84	500
50670	25T6.5/CL/7.5M/E17/145V/STD	25	E17	145	Clear	7 500	C-8	150	5.5 140	3.3 84	120
50673	25T6.5/F/7.5M/E17/145V/STD	25	E17	145	Frost	7 500	C-8	145	5.5 140	3.3 84	500
50680	40T6.5/CL/5M/E17/130V/STD	40	E17	130	Clear	5 000	C-8	300	5.4 137	3.3 84	500
52191	40T6.5/F/5M/E17/130V/STD	40	E17	130	Frost	5 000	C-8	280	5.5 140	3.3 84	500
T7											
52195	15T7/CL/1.5M/BA15d/120V/STD	15	BA15d	120	Clear	1 500	C-7A	100	2.3 59	1.3 33	1 000
52196	15T7/F/1.5M/BA15d/130V/STD	15	BA15d	130	Frost	1 500	C-7A	98	2.3 59	1.3 33	1 000
52192	15T7/CL/1.5M/E12/120V/STD	15	E12	120	Clear	1 500	C-7A	100	2.3 59	1.5 38	1 000
52194	15T7/CL/1.5M/E17/120V/STD	15	E17	120	Clear	1 500	C-7A	100	2.3 59	1.5 38	1 000
14692	15T7/INT/CL/120V	15	E17	120	Clear	1 500	C-7A	85	2.5 63	1.5 38	1 000
52201	25T7/CL/1.5M/E12/130V/STD	25	E12	130	Clear	1 500	C-7A	150	2.3 59	1.5 38	1 000
T8											
52198	25T8/CL/1.5M/BA15d/120V/STD	25	BA15d	120	Clear	1 500	C-7A	220	2.6 65	1.6 41	1 000
52199	25T8/F/1.5M/BA15d/130V/STD	25	BA15d	130	Frost	1 500	C-7A	210	2.6 65	1.6 41	1 000
52200	25T8/CL/1.5M/E12/120V/STD	25	E12	120	Clear	1 500	C-7A	220	2.6 65	1.6 41	1 000
52197	25T8/CL/1.5M/E17/120V/STD	25	E17	120	Clear	1 500	C-7A	220	2.6 65	1.6 41	1 000
14695	25T8/F/1.5M/E17/120V	25	E17	120	Frost	1 500	C-7A	210	2.6 65	1.6 41	1 000
14794	40T8/CL/BA15d/120V	40	BA15d	120	Clear	2 500	C-8	425	11.9 302	1.6 41	1 000
52202	40T8/CL/1M/120V/STD	40	E26	120	Clear	1 000	C-8	410	11.9 302	1.6 41	100
14699	40T8/F/2.5M/120V	40	E26	120	Frost	2 500	C-8	425	11.9 302	1.6 41	200
14696	75T8/CL/2.5M/120V	75	E26	120	Clear	2 500	C-8	890	11.9 302	1.6 41	200
T10											
50923	15T10/CL/3M/130V/STD	15	E26	130	Clear	3 000	C-5V	90	5.0 127	2.8 70	360
50924	15T10/F/3M/130V/STD	15	E26	130	Frost	3 000	C-5V	95	5.0 127	2.8 70	360
50925	25T10/CL/3M/130V/STD	25	E26	130	Clear	3 000	C-5V	170	5.0 127	2.8 70	360
50928	25T10/F/3M/130V/STD	25	E26	130	Frost	3 000	C-5V	160	5.0 127	2.8 70	360
10952	6.6 AMPS/T10/1P 30W P28S	30	P28s	6.6 A	Clear	1 000	C-2V	400	3.9 99	2.8 70	60
50926	40T10/CL/3M/130V/STD	40	E26	130	Clear	3 000	C-5V	250	5.0 127	2.8 70	360
50929	40T10/F/3M/130V/STD	40	E26	130	Frost	3 000	C-5V	240	5.0 127	2.8 70	360
10953	6.6 AMPS/T10/1P 45W P28S	45	P28s	6.6 A	Clear	1 000	C-2V	675	3.9 99	2.8 70	60
T10 (Suitable for use base up)											
50927	60T10/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-5V	420	5.0 127	2.8 70	360
50930	60T10/F/3M/130V/STD	60	E26	130	Frost	3 000	C-5V	410	5.0 127	2.8 70	360
T10 High Output											
50164	15T10/CL/3M/HO/130V/STD	15	E26	130	Clear	3 000	C-8	95	5.4 137	3.3 84	360
50149	25T10/CL/3M/HO/130V/STD	25	E26	130	Clear	3 000	C-8	210	5.4 137	3.3 84	360
50131	25T10/F/3M/HO/130V/STD	25	E26	130	Frost	3 000	C-8	200	5.4 137	3.3 84	360
50129	40T10/CL/3M/HO/130V/STD	40	E26	130	Clear	3 000	C-8	350	5.4 137	3.3 84	360
T10 High Output (Suitable for use base up)											
50132	40T10/F/3M/HO/130V/STD	40	E26	130	Frost	3 000	C-8	340	5.4 137	3.3 84	360
50130	60T10/CL/3M/HO/130V/STD	60	E26	130	Clear	3 000	C-8	450	5.4 137	3.3 84	360
50133	60T10/F/3M/HO/130V/STD	60	E26	130	Frost	3 000	C-8	440	5.4 137	3.3 84	360