

Project: \_\_\_\_\_ Type: \_\_\_\_\_  
 Drawn by: \_\_\_\_\_ Catalogue #: \_\_\_\_\_ Date: \_\_\_\_\_

## Individual Spec Sheet

# PAR38

## 6 COLOR SELECTABLE

### ORDERING INFORMATION

**Order code:** 69760  
**Model number:** PAR38/8W/COLORSELECT/40/ND/STD  
**UPC:** 069549029811  
**Case quantity:** 12

### PHYSICAL DATA

**Dimensions:** 5 1/8 (MOL) x 4 3/4" (DIA) (130 x 120mm)  
**Shape:** PAR38  
**Base:** E26  
**Finish:** Clear


### PERFORMANCE DATA

**Watts (W):** 8  
**Traditional Equivalent (W):** 65  
**Volts (VAC):** 120  
**Color selectable:** Red, Green, Blue, Yellow, Orange and White  
**Efficacy (lm/W):** 88  
**CRI:** 80  
**Life L70 (h)<sup>1</sup>:** 15 000  
**Beam angle (°):** 40  
**Power factor:** ≥0.5  
**Frequency (Hz):** 60  
**Operating temp. range:** - 30 °C / - 22 °F to 35 °C / 95 °F  
**Applications:** Indoor/Outdoor

<sup>1</sup> Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations.



### DIMENSIONS



**2**  
yrs  
warranty

  
non  
dimmmable

  
wet  
location



ICES  
005



enclosed  
fixture

**RoHS**

  
CERTIFIED

**FC**

This lighting equipment meets requirements of ICES-005 issue 5 class B for use in residential applications.  
 Data is based upon tests performed in a controlled environment.  
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.