

Project: _____

Type: _____

Drawn by: _____ Catalogue #: _____

Date: _____

Individual Spec Sheet

LED REFLECTORS

CHOICE

PAR38

ORDERING INFORMATION

Order code: 70260
 Model number: P38/S3/15W/40K/40/CHOICE/STD
 UPC: 069549033283
 Case quantity: 6

PHYSICAL DATA


Dimensions: MOL: 130 mm (5 1/8")
 DIA: 120 mm (4 3/4")
 Shape: PAR38
 Base: E26
 Finish: Lens: Clear

PERFORMANCE DATA

Watts (W):	15	Beam angle (°):	40°
Traditional equivalent (W):	100	CBCP (cd):	1 993
Volts (V AC/DC):	120	Power factor:	0.7
Color temperature (K) ¹ :	4 000	Input Current (mA):	175
Lumen output (lm) ² :	1 200	Frequency (Hz):	60
Efficacy (lm/W):	70	Lens material:	Plastic
CRI:	90	Housing Material:	Plastic
Dimmable	Yes	Application:	Indoor
Life L70 (h) ³ :	25 000	Operating temp. range:	-40 °C / -40 °F to 45 °C / 113 °F

¹ Typical colour temperature range: +/- 5 %.² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.³ Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 extrapolations.

DIMENSIONS

COMPATIBLE DIMMERS¹

Brand	Model
LUTRON	HCL453P, DVCL-153P, CTCL-153P, SELV-300P
COOPER	DAL06P, AAL06
LEVITON	RH730PTUTC

¹ This table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Some dimmers may require more than one product for stable operation. Stanpro recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation.

Dimming performance might be impacted when using the above dimmers with only one lamp. Full performance achieved when using two or more lamps.



3^{yrs}
 warranty



dimmable

wet
locationenclosed
fixtureICES
005

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.
 Data is based upon tests performed in a controlled environment.
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.