



TMP TEMPORARY WORK LIGHT

EiKO's temporary work lights provide easy operation, high lumen output, and rugged construction for demanding environments. These fixtures can be daisy chained allowing multiple fixtures to be connected from a single outlet.



RoHS
Compliant



IP64



project name	type
catalog number	voltage
approved by	date



FEATURES AND BENEFITS

PERFORMANCE

- Lumen packages: 12,000 and 18,000 lumens
- Replaces 250W and 400W HID fixtures
- Input Voltage: 120V
- Efficacy up to 120 LPW
- 5A overload protection
- CCT: 5000K for bright light in
- 360° light distribution
- Lumen Maintenance 70% (L70) > 50,000 hours
- Power Factor: 0.9
- THD: <20%
- Operating Temperature: -22°F to 140°F (-30°C to 60°C)
- IP64 Rated

APPLICATIONS

- Task Lighting
- Commercial
- Work Areas
- Construction
- Temporary highway

INSTALLATION

- M8 Screw Threads in lamp base for installation flexibility.
- Includes 6' power cord with plug and detachable, retractable handle. Handle has a hole for hanging the fixture.
- Eyebolt included in package.
- Installs base up, base down, or in a horizontal plane.
- **Linkable, can be daisy chained from a single outlet (100W = 6 units max, 150W = 4 units max)**

CONSTRUCTION

- Polycarbonate lens for LED module.
- Protective aluminum cage for use in demanding environments.

SMART DRIVER OPERATION

- 600W/5A overload protection.
- For example: With the 100W unit, maximum 6 units can be daisy chained. Connecting a 7th unit, triggers the driver to automatically shut down the last 6 units while keeping the first unit illuminated. Once the 7th unit is disconnected, all 6 units automatically light back up.

AVAILABLE MODELS

ORDER	ORDER CODE	MODEL	WATTS (W)	COLOR TEMPERATURE (CCT)	LUMEN OUTPUT (lm)	INPUT VOLTAGE (VAC)
	11391	LED100WTMP50K-G8	100W	5000K	12,000 lm	120V
	11392	LED150WTMP50K-G8	150W	5000K	18,000 lm	120V

PRODUCT DIMENSIONS

