


ORDERING INFORMATION

Order code: 10041
 Description: BHPS0250/347/480/600/C/CWI/H/K
 UPC: 69549100411



SPECIFICATIONS

Ballast type: Magnetic high pressure sodium
 Ballast style: Core and coil
 Circuit type: CWI
 ANSI code: S50
 Input voltage (V): 347/480/600
 Input frequency (Hz): 60
 Line volt regulation: ± 10 %
 Line watt regulation: Within trapezoid
 Insulation class: H (180°)



Input voltage (V)	Operating current (A)	Open circuit current (A)	Starting current (A)	Rated lamp watts (W)	Input watts (W)	OCV (V)	Dropout voltage (V)	UL 1029 code	Fuse rating (A)	Input current (A)	Power factor	Starting temperature
347	0.90	0.47	0.35	250	290	190	240	B	3	0.19 - 0.31	0.90	-40°F / -40°C
480	0.65	0.42	0.26	250	290	190	330	A	2	0.14 - 0.23	0.90	-40°F / -40°C
600	0.52	0.31	0.21	250	290	190	410	A	2	0.10 - 0.17	0.90	-40°F / -40°C

HIGH POTENTIAL TEST (V)


1 minute:	2 200
2 seconds:	2 650
OCV test:	170 - 210
Short circuit:	3.60 - 4.20

BALLAST DIMENSIONS


Dimension A:	1.90"
Dimension B:	3.75"
Lead Lengths:	12.00"
Weight (lbs):	13.00

WIRING DIAGRAM


Ground ballast core



BRACKET



CAPACITOR



IGNITOR

