

# Wall Cylinder

30W | RGBW | 120-277V



Suitable for indoor and outdoor applications including retail stores, event spaces, hospitality venues, condominiums, building entrances, and more!

120-277V

Powder Coat Finish  
black

Remote Control Included  
for colour and operating  
mode selection



16 Colours  
and 5 operating modes

Cylinder Rings Illuminate

Direct / Indirect  
50% uplight, 50% downlight

Packaged in  
Eco-friendly  
Packaging  
without plastic



## TECHNICAL DATA

### LIGHT SPECIFICATIONS

Efficacy*	41 lm/W
CCT	RGBW
CRI	>80
Distribution	Direct / Indirect (50% downlight, 50% uplight)
Beam Angle	60°
L70 Life	50,000 hrs
Warranty	10-year
Factory Settings	30W   White

\*When set to White

LUMEN OUTPUT				
	Red	Green	Blue	White
<b>30W</b>	270 lm	899 lm	191 lm	1230 lm

### APPROVALS & LISTINGS

cUL	E482965
-----	---------

### DIMENSIONS AND WEIGHTS

Fixture Weight	3.13 lbs
Fixture Dimensions	4.72 x 10.35 x 4.76 in
Master Carton Qty	6
Master Carton Weight	22.84 lbs
Master Carton Dimensions	16.14 x 11.81 x 11.42 in
Carton Qty	1
Carton Weight	3.44 lbs
Carton Dimensions	11.22 x 5.12 x 5.31 in

### ELECTRICAL

Wattage	30W
Voltage	120-277V
Current	0.2A
Surge Protection	6kV
Auxiliary Output	N/A
Power Factor	0.9
THD	≤15%
Operating Temp	-40 to 50°C

### CONSTRUCTION

Housing	Die-Cast Aluminum
Lens	Glass
Finish	Powder Coated
Finish Colour	Black
IP Rating	IP65

### DIMENSIONAL DRAWINGS (IN)

