

Safety Max™ Lamps



Incandescent Lamps

With STANDARD Safety Max™, you protect the products of the production line, without sacrificing lumen output. Should a Safety Max™ lamp break, virtually all glass, mercury, metal and phosphors are contained by the safety coating. Disposal and lamp changes are also easy and safe.

Therefore, you can prevent contamination, minimize risk and avoid your business being shut down.

Order code	Description	Watts (W)	Base	Volts (V)	Lumens at 120 V (lm)	Average life (hrs)	Filament type	Coating	Finish	MOL (in.) (mm)		LCL (in.) (mm)		Case qty (inner/master)
A15														
46063	25A15/F/5M/130V/STD SM	25	E26	130	150	5 000	C-9	Mylon	Frost	3.5	89.0	2.4	60	6/60
67723	40A15/F/5M/130V/HIGH TEMP/STD SM	40	E26	130	320	5 000	C-9	PFA	Frost	3.4	86.0	2.4	62	6/60
67724	40A15/F/5M/130V/LOW TEMP/STD SM	40	E26	130	320	5 000	C-9	Silicone	Frost	3.4	86.0	2.4	62	6/60
69671	40A15/F/6.5M/250V SM	40	E26	250	300	6 500	C-9	PFA	Frost	3.5	89.0	2.4	60	1/100
A19														
10123	25A19/F/6M/130V/STD SM	25	E26	130	168	6 000	C-9	Silicone	Frost	4.2	108	2.9	73	24/120
51092	60A19/F/6M/130V/STD SM	60	E26	130	410	6 000	C-9	Silicone	Frost	4.2	108	3.1	79	6/24
10131	60A19/F/RS/130V/STD SM	60	E26	130	350	5 000	C-9	Silicone	Frost	4.2	108	3.1	79	6/24
10129	75A19/F/RS/130V/STD SM	75	E26	130	540	5 000	C-9	Silicone	Frost	4.2	108	3.1	79	6/24
A21														
10372	100A21/F/5M/130V/STD SM	100	E26	130	1 030	5 000	C-9	Silicone	Frost	5.3	135	3.5	90	6/24
A23														
50912	200A23/F/5M/130V/STD SM	200	E26	130	1 640	5 000	C-9	Silicone	Frost	6.2	157	5.1	128	20/60
10125	200A23/F/RS/130V/STD SM	200	E26	130	2 335	5 000	C-9	Silicone	Frost	6.3	160	4.6	117	6/24
B10														
10119	60B10/CL/3M/130V/STD SM	60	E26	130	550	3 000	C-9	Silicone	Clear	3.9	99	2.1	53	6/24
BR40														
69675	250BR40/IR/CL/6M/120V SM	250	E26	120	2 400	6 000	C-9	PFA	Clear	6.5	165	4.3	108	1/12
PS25														
10254	150PS25/F/RS/130V/STD SM	150	E26	130	1 120	3 000	C-9	Silicone	Frost	6.9	176	5.3	133	20/60
10255	200PS25/F/RS/130V/STD SM	200	E26	130	1 640	3 000	C-9	Silicone	Frost	6.9	176	5.3	133	6/24
10126	300PS25/F/5M/130V/STD SM	300	E26	130	2 460	5 000	C-9	Silicone	Frost	6.9	176	5.3	133	6/24
R12 - R40														
11813	20R12/CL/13V/ BA15S/SM	20	BA15s	13	N/A	300	C-8	Mylon	Clear	2.6	66	N/A	N/A	10/50
69673	250R40/IR/R/6M/120 130V/STD SM	250	E26	120	N/A	6 000	C-9	PFA	Red	6.6	167	3.9	99	1/12
69674	375R40/IR/CL/6M/120V SM	375	E26	120	N/A	6 000	C-9	PFA	Clear	7.6	193	4.2	106	1/12