

PROJECT:

DISTRIBUTOR:

DRAWN BY:

CATALOGUE #:

CONTRACTOR:

DATE:

TYPE:

PO:

STANDARD[®]

SPEC SHEET

ORDERING INFORMATION

Order Code: 70636
Model Number: A19/S7/9.8W/30K/STD 4P
UPC: 069549036239
Case Quantity: 12 x 4 pack

PHYSICAL DATA

Base: E26
Type: A19 4 pack

PERFORMANCE DATA

Watts (W): 9.8
Traditional Equivalent (W): 60
Volts (V AC): 120
Color temperature (K)¹: 3 000
Lumen Output (lm)²: 800
Efficacy (lm/W): 82
CRI: 80
Dimmable: Yes
Life L70 (h)³: 25 000
Beam Angle: 220
Power Factor: 0.81
Frequency (Hz): 60
Input Current (A): 90
Operating Temp. Range: -30 °C to 45 °C (-22 °F to 113 °F)
Warranty: 3 Years

¹ Typical colour temperature range: +/- 5 %.² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.³ Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 extrapolations.COMPATIBLE DIMMERS¹


Brand	Model
Lutron	AYCL-253P, CTCL-153P, DVCL-153P, DVCL-253P, DVELV-300P, HCL-453P, MACL-153P, PD-6WCL, SELV-300P
Cooper	AAL06, DAL06P, SAL06P3
Leviton	6674, DDMX1, DSL06-1LZ, DSM10-1LZ, IPE04-1LZ, IPL06
Legrand	RH730PTUTC

Dimming range: 10 %-100 %

Dimming performance might be impacted when using the above dimmers with only one lamp. Full performance achieved when using two or more lamps.

¹ This table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Some dimmers may require more than one product for stable operation. Stanpro recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation.

TECHNICAL DRAWING

3 YEARS
WARRANTY

DIMMABLE

ENCLOSED
FIXTUREUL
CERTIFIED

This lighting equipment meets requirements of ICES-005 issue 5 class B for use in residential applications.

Data is based upon tests performed in a controlled environment.

Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.