



FUSION SERIES **FLOOD LIGHTS**

Built to Perform. Engineered to Endure.

FUSION

FLOOD LIGHTS



KEY FEATURES

Power Selectable

40W / 60W / 80W
100W / 125W / 150W
200W / 250W / 300W

3CCT Selectable

3000K / 4000K / 5000K

120-347V Universal Driver

0-10V dimming

3 Distribution Types per Luminaire

5H5V / 6H6V / 7H6V
(optic adjustment tool included)

IK07 and IP65 Rated

Built-in Photocell
switch off to disable

**All Models Available
in Black and Bronze**



MOUNTING MADE EASY

Choose from a variety of mounting options sold separately to minimize waste, reduce storage and shipping needs, and save you money. Customize even further with pole accessories like our 2-head or 3-head bullhorns. Note: Slip Fitter is required and sold separately for use with pole accessories.



BEAM ANGLE ADJUSTABLE

Effortlessly configure output settings on-site with simple, built-in switches that let you modify beam angle, wattage, and CCT to meet the specific needs of any application. Designed for quick, hassle-free adjustments without the need for special tools, it streamlines setup and enhances project flexibility.



FOCUSED ILLUMINATION

The goal is focused illumination without lighting the entire site. Floodlights are designed to tilt—this is where they shine:

- Lighting building exteriors
- Securing loading docks
- Illuminating sports fields
- Highlighting signage or façades




FUSION | FLOOD LIGHTS

Illuminate large outdoor areas including parking lots, building exteriors, sports fields, and more!



Fixtures	Wattage	CCT	Voltage	Lumens	Finish
FLF-80W-3P-3CCT-3B-UD-BZ FLF-80W-3P-3CCT-3B-UD-BK	40W / 60W / 80W	30K / 40K / 50K	120-347V	7060-11243 lm	Bronze Black
FLF-150W-3P-3CCT-3B-UD-BZ FLF-150W-3P-3CCT-3B-UD-BK	100W / 125W / 150W	30K / 40K / 50K	120-347V	15167-21936 lm	Bronze Black
FLF-300W-3P-3CCT-3B-UD-BZ FLF-300W-3P-3CCT-3B-UD-BK	200W / 250W / 300W	30K / 40K / 50K	120-347V	29696-46413 lm	Bronze Black

Choose your Mount!
Available in
Bronze and Black
(sold separately)



Fixed Mount



Multi Mount



Pole Mount



Trunnion Mount



Slip Fitter



Yoke Mount



Compatible with standard 3-pin NEMA photocells when the JL-200 is installed (sold separately).



For information on the complete series including IES files, spec sheets, and more, visit www.csc-led.com



Check out our
YouTube channel for
more information on
our products!

Lumen Output Tables

and Product Numbers

FLF-80W-3P-3CCT-3B-UD-XX*

	3000K	4000K	5000K
40W	7060 lm	7407 lm	7280 lm
60W	8860 lm	9377 lm	9096 lm
80W	10694 lm	11243 lm	10835 lm

FLF-150W-3P-3CCT-3B-UD-XX*

	3000K	4000K	5000K
100W	15167 lm	15830 lm	15438 lm
125W	17951 lm	19313 lm	18702 lm
150W	21141 lm	21936 lm	21061 lm

FLF-300W-3P-3CCT-3B-UD-XX*


	3000K	4000K	5000K
200W	29696 lm	31741 lm	31461 lm
250W	35587 lm	38136 lm	36884 lm
300W	41725 lm	45074 lm	46413 lm

*Where -XX denotes finish colour

SELECTION SWITCHES & PHOTOCELL OPTIONS



Beam Angle Selector



Power, CCT, & Photocell
Selector Switches



Blanking Plate with
1/2" Knockout





BC BRANCH

1140-2375 Fremont St
Port Coquitlam, BC V3B 0N9
(778) 730-0448

AB BRANCH

13-2355 52 Ave SE
Calgary, AB T2C 4X7
(403) 907-0212

ON HEAD OFFICE

8-540 Jamieson Pkwy
Cambridge, ON N3C 0G5
(519) 880-9833